AP-203

REVIEW FORM

AIRPAX P/N: AP12-26130-2

CUSTOMER P/N:

DATE: 10/23/90 SALES: BM

CUSTOMER: Marconi (Italy)

REVISION: NP

PURPOSE: ☐ QUOTE ☐ NEW REV. ☐ NEW REV. WITH ORDER ☐ NEW PRINT WITH ORDER ☐ ORDER

UL / CSA ☐
SEV ☐
MIL-C-39019 ☐
☐
☐

AUX. SWITCH
☐ YES, IN POLE ____
☒ NO
☐ R STD. AP
☐ RC CANE HOOK

TERMINALS:
☐ ¼ QUICK CONN.
☐ SCREW
☐ SCREW w/ BLOCK
☒ CANE HOOK

DASH NO.	POLE NO.	I	V RATED V, or TRIP VOLTS	Hz	DELAY	BASIC CONSTRUCTION
	1	5.0	240	50/60	61	Series
	2	5.0	240	50/60	61	Series
		.				
		.				
		.				
		.				
		.				
		.				

203 HNDL. COLOR & MKGS ____
BODY COLOR ____
ILLUMINATION ____

203 MTG. HDWRE.
☐ NO
☐ STD.
☐ SPECIAL

MARKING REQUIREMENTS	YES	NO
CUSTOMER P/N	☐	☒
MFGR. IDENT. NO. 81541	☐	☒
PAPER LABEL	☐	☒
PAINTED MARKINGS	☒	☐
SCHEMATIC P/N ____	☐	☒
SPECIAL TERMINAL MKGS.	☐	☒
MARKING PROC. P-108 MIL	☐	☒
ADDITIONAL REQUIREMENTS		
SEAL SCREW	☒	☐

SPECIAL REQUIREMENTS AND INSTRUCTIONS *(FOR ENGINEERING USE ONLY)*

1st Review

SPECIAL REQUIREMENTS AND INSTRUCTIONS *(FOR MKT. USE ONLY)*

Customer requires voltage rating of 240 VAC ± 10%

See FAX from Elcam dated Oct 23, 90

MARKETING REFERENCE INFORMATION:

FOR ENGINEERING USE		SALES DECISION	
CUSTOMER PRINT READS	EXCEPTIONS REQUESTED	PRINT	EXCEPTION

PRINT REVIEWED BY: KJ

DATE: 10/26/90

☐ QA TO EVALUATE SPECIAL TEST REQUIREMENTS

INITIALS & DATE:

☐ SPECIAL SHIPPING REQUIREMENTS

MKT. INITIALS & DATE: BM 10/29/90

ENG. ACKNOWLEDGE INITIALS & DATE

C-1525 8/83 23098