

[Request a Sample](#)

Customer Specification

PART NO. DR04AW105

Construction

Cordset Configuration	
End 1	M12M
End 2	M12F 90 Degree
Insert	Black TPU
Mold Color	Black TPU
Contact	Copper Alloy, Gold Plated
Coupling Nut	Copper Alloy, Nickel Plated

Cordage Construction	
Cable Construction	4 X 1 COND
Conductor	22 (26/26) AWG BC
Jacket	-40 PVC
Jacket Color	SLATE
OD	0.189
Insulation	0.011" Wall, Nom. SR-PVC
Insulation Colors	Brown, White, Blue, Black

Applicable Specifications

Cordset Applicable Specifications	
UL	ANSI/UL 2238, Cable Assembly Extension
Ingress Protection	IP67, IP68/NEMA 6P
CSA	CSA-C22.2 No. 182.3, Special Use Attachment Plugs, Receptacles and Connectors cRU, UL File Number E485156

Cordage Applicable Specifications			
UL			
AWM/STYLE 10002	105°C / 300 V _{RMS}		AWM/STYLE 2661
AWM/STYLE 2661			
			CSA International

Environmental

CE: EU Directive 2011/65/EU (RoHS3):

All materials used in the manufacture of this part meet the requirements of European Directive 2011/65/EU (RoHS Directive) of the European Parliament and the amending Directive 2015/863/EU. Exemption used: 6c

REACH Regulation (EC 1907/2006):

This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item. For up-to-date information, please see Alpha's REACH SVHC Declaration.

Properties

Physical & Mechanical Properties

Temperature Range	-40 to 105°C(static), -15 to 105°C (dynamic)
Bend Radius	7X Cable Diameter(static), 10X Cable Diameter(dynamic)
Pull Tension	20.4 Lbs, Maximum

Other

Available Lengths

355- 0.6 Meters
 356- 1.0 Meters
 357- 3.0 Meters
 358- 5.0 Meters
 359- 10 Meters
 400- 15 Meters
 401- 20 Meters

www.alphawire.com

Alpha Wire | 711 Lidgerwood Avenue, Elizabeth, NJ 07207

Tel: 1-800-52 ALPHA (25742)

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE - CONFIDENTIAL AND PROPRIETARY

Notice to persons receiving this document and/or technical information. This document is confidential and is the exclusive property of ALPHA WIRE, and is merely on loan and subject to recall by ALPHA WIRE at any time. By taking possession of this document, the recipient acknowledges and agrees that this document cannot be used in any manner adverse to the interests of ALPHA WIRE, and that no portion of this document may be copied or otherwise reproduced without the prior written consent of ALPHA WIRE. In the case of conflicting contractual provisions, this notice shall govern the status of this document. ©2013 ALPHA WIRE - all rights reserved.



EU ROHS CERTIFICATE OF COMPLIANCE

To Whom It May Concern:

Alpha Wire Part Number: DR04AW105

DR04AW105 , RoHS-Compliant Commencing With 9/21/2016 Production

Note: all colors and put-ups

This document certifies that the Alpha part number cited above is manufactured in accordance with Directive 2011/65/EU of the European Parliament, better known as the RoHS Directive (commonly known as RoHS 2), with regards to restrictions of the use of certain hazardous substances used in the manufacture of electrical and electronic equipment. This certification extends to amending Directive 2015/863/EU which expanded the list of restricted substances to 10 items (commonly known as RoHS 3). The reader is referred to this Directive for the specific definitions and extents of this Directive. **RoHS Compliance on this item is based on Exemption 6c, "Lead in Copper Alloys"**.

Substance	Maximum Control Value
Lead	0.1% by weight (1000 ppm)
Mercury	0.1% by weight (1000 ppm)
Cadmium	0.01% by weight (100 ppm)
Hexavalent Chromium	0.1% by weight (1000 ppm)
Polybrominated Biphenyls (PBB)	0.1% by weight (1000 ppm)
Polybrominated Diphenyl Ethers (PBDE) ,	
Including Deca-BDE	0.1% by weight (1000 ppm)
Bis(2-Ethylhexyl) phthalate (DEHP)	0.1% by weight (1000 ppm)
Benzyl butyl phthalate (BBP)	0.1% by weight (1000 ppm)
Dibutyl phthalate (DBP)	0.1% by weight (1000 ppm)
Diisobutyl phthalate (DIBP)	0.1% by weight (1000 ppm)

The information provided in this document and disclosure is correct to the best of Alpha Wire's knowledge, information and belief at the date of its release. The information provided is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it will become part of. The intent of this document is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Authorized Signatory for the Alpha Wire:

Dave Watson, Director of Engineering & QA

5/24/2019

Alpha Wire

711 Lidgerwood Ave.

Elizabeth, NJ 07207

Tel: 1-908-925-8000