



[+ TERMINALS & SPLICES](#)
[CRIMP TERMINAL HOUSINGS](#)



✓ Active

TE CONNECTIVITY (TE)

4P POSITIVE LOCK HSG, MARK II

[Positive Lock | 250](#)

1969761-1

TE Internal Number: 1969761-1

[EU RoHS Compliant](#)

[EU ELV Compliant](#)

Terminal Style Receptacle

Insulated Yes

Housing Type Receptacle Housing

Number of Positions 4

Terminal Orientation Straight

[↓ PRODUCT DRAWING](#)
English

DOCUMENTATION

Product Drawings

4P POSITIVE LOCK HOUSING, MARK II

PDF

English

Agency Approvals

UL Report

POSITIVE LOCK AND POSITIVE LOCK EX SERIES REPORT

PDF

English

FEATURES

Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Insulated Yes

Product Type Terminal Housing

Terminates To Wire/Cable

Configuration Features

Number of Positions 4

Body Features

Housing Color Natural

Mating Retention With

Mating Alignment With

Contact Features

Terminal Style Receptacle

Terminal Orientation Straight

Mechanical Attachment

Mating Retention Type Latch

Housing Features

Housing Type Receptacle Housing

Housing Material Nylon

Dimensions

Accepts Wire Insulation Diameter Range (in) .193

Usage Conditions

Operating Temperature Range -40 – 130 °C [-40 – 266 °F]

Industry Standards

UL Flammability Rating UL 94V-0

Packaging Features

Packaging Method Box

Statement of Compliance

Statement of Compliance

PDF
