


| | |
|---------------------|--|
| Product description | M5 Female cable connector, Contacts: 3, unshielded, moulded on the cable, IP67, UL 2238, M5x0.5, PUR, black, 3 x 0.25 mm², 2 m |
| Area | series 707 |
| Part no. | 77 3450 0000 50003-0200 |


Illustration



Scale drawing



Contact arrangement (Plug-in side)



Technical data

General features

| | |
|---------------------------|---|
| Part no. | 77 3450 0000 50003-0200 |
| | Alternative part no.: 79 3102 32 03 |
| Connector design | Female cable connector |
| Type standard | DIN EN 61076-2-105 |
| Cable length | 2 m (Standard 2 m and 5 m. Other lengths are available on request.) |
| Version | Connector socket straight |
| Connector locking system | screw |
| Termination | moulded on the cable |
| Degree of protection | IP67 |
| Connection cross-section | 0.25 mm ² / AWG 24 |
| Temperature range from/to | -25 °C / 80 °C |
| Mechanical operation | > 100 Mating cycles |
| Weight (g) | 56.66 |
| Customs tariff number | 85444290 |
| Country of Origin | DE |

Electrical parameters

| | |
|---------------------------|---------------------|
| Rated voltage | 60 V |
| Rated impulse voltage | 800 V |
| Rated current | 1.0 A |
| Insulation resistance | > 10 ⁸ Ω |
| Pollution degree | 3 |
| Overvoltage category | II |
| Insulating material group | I |
| EMC compliance | unshielded |

Product data sheet

Automation technology - Sensors and actuators



| | |
|---------------------|--|
| Product description | M5 Female cable connector, Contacts: 3, unshielded, moulded on the cable, IP67, UL 2238, M5x0.5, PUR, black, 3 x 0.25 mm², 2 m |
| Area | series 707 |
| Part no. | 77 3450 0000 50003-0200 |

Material

| | |
|-----------------------|--------------------------------------|
| Housing material | PUR |
| Contact body material | PUR |
| Contact material | CuSn (bronze) |
| Contact plating | Au (gold) |
| Locking material | CuZn (brass) |
| REACH SVHC | CAS 7439-92-1 (Lead) |
| SCIP number | df5076cf-7022-4cd0-adc4-488886bc24e7 |

Authorization/approvals

| | |
|-----------|---------|
| Approvals | UL 2238 |
|-----------|---------|

Classifications

| | |
|-------------|-------------|
| eCl@ss 11.1 | 27-06-03-11 |
| ETIM 9.0 | EC002638 |

Cable data - Structure of the cable

| | |
|------------------------|--------------------------|
| Cable diameter | 3.7 mm |
| Cross section | 3 x 0.25 mm ² |
| Sheath material | PUR |
| Single-lead insulation | PVC |
| Single-lead structure | 32 x 0.10 mm |
| Cable color | black |

Cable data - Electrical properties

| | |
|----------------------|----------------|
| Conductor resistance | 79 Ω/Km (20°C) |
|----------------------|----------------|

Cable data - Mechanical properties

| | |
|------------------------------|----------|
| Bending radius, fixed cable | ≥ 5 x Ø |
| Bending radius, moving cable | ≥ 10 x Ø |

Cable data - Thermal properties

| | |
|---|----------------|
| Temperature range cable in move from/to | -5 °C / 80 °C |
| Temperature range cable fixed from/to | -25 °C / 80 °C |

Cable data - Other features

| | |
|--------------|-----|
| Halogen free | yes |
|--------------|-----|

| | |
|---------------------|--|
| Product description | M5 Female cable connector, Contacts: 3, unshielded, moulded on the cable, IP67, UL 2238, M5x0.5, PUR, black, 3 x 0.25 mm², 2 m |
| Area | series 707 |
| Part no. | 77 3450 0000 50003-0200 |

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

To protect against unintentional opening of the connector, the thread between the housing and the connector head must be secured with a suitable cyanoacrylate adhesive when used in circuits with voltages dangerous to the touch. This does not apply to connectors used in SELV and PELV circuits according to IEC 61140 (EN 61140, VDE 0140-1).

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 50 cNm).

DECLARATION FROM THE MANUFACTURER

For part no.: 77 3450 0000 50003-0200

08/07/2025

With regard to the

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

With the REACH regulation, the EU has created a uniform system for the Registration, Evaluation, Authorisation and restriction of CHEMicals – or REACH. The purpose of this regulation is to ensure a high level of protection of human health and the environment.

Franz Binder GmbH & Co. Elektrische Bauelemente KG hereby confirms that it acts as a downstream user (producer of products) according to the aforementioned regulation.

We obtain all raw materials and/or preparations, from which the connectors are made, from suppliers who have already registered or pre-registered all substances, including those present in the preparations. The products supplied by the company are not subject to registration.

With regard to Article 33(1) of the REACH regulation, Franz Binder GmbH & Co. Elektrische Bauelemente KG complies with its information obligations:

An up-to-date candidate list (candidate list of substances of very high concern for authorisation, as of 25/06/2025 see: <https://echa.europa.eu/de/candidate-list-table>) in accordance with Article 59 (1, 10) of the regulation (EC) No 1907/2006 (REACH) has been published.

The aforementioned article includes the following substances from the up-to-date candidate list in concentrations of more than 0,1 percent by mass:

- CAS 7439-92-1 (Lead)

Please refer any questions to our Product Compliance Team:

Product-Compliance@binder-connector.de

DECLARATION FROM THE MANUFACTURER

For part no.: 77 3450 0000 50003-0200

08/07/2025

With regard to the

COMMISSION DELEGATED DIRECTIVE (EU) 2015/863 of 31 March 2015

**amending Annex II to Directive 2011/65/EU of the European Parliament and of the Council as regards
the list of restricted substances**

Directive 2011/65/EU stipulates provisions on the restriction of the use of hazardous substances in electrical and electronic equipment (EEE) with a view to contributing to the protection of human health and the environment, including the environmentally sound recovery and disposal of EEE waste.

ANNEX II

Restricted substances referred to in Article 4(1) and maximum concentration values tolerated by weight in homogeneous materials

Lead (0,1%) mercury (0,1%) cadmium (0,01%) hexavalent chromium (0,1%) polybrominated biphenyls (PBB) (0,1%) polybrominated diphenyl ethers (PBDE) (0,1%) bis(2-ethylhexyl) phthalate (DEHP) (0,1%) butyl benzyl phthalate (BBP) (0,1%) dibutyl phthalate (DBP) (0,1%) diisobutyl phthalate (DIBP) (0,1%)

Franz Binder GmbH & Co. Elektrische Bauelemente KG hereby confirms that it complies with all standard articles of the aforementioned Directive. Our products do not contain any of the specified prohibited substances above the maximum permitted concentrations specified therein, taking into account the exemptions in Annex III of Directive 2011/65/EU.

- Complies with RoHS III with exemption 6c

Please refer any questions to our Product Compliance Team:

Product-Compliance@binder-connector.de

MANUFACTURER'S DECLARATION

For part no.: 77 3450 0000 50003-0200

08/07/2025

with regard to

Declaration of compliance with China RoHS – Components

We herewith declare the compliance of this product with the Chinese marking requirements. This product can be recycled and used safely during its environmentally friendly use period of 50 years. These articles will be sold as components only for manufacturing. According to the Electronic Industry Standard SJ/T 11364-2014 it needs not to be marked with Environmentally Friendly Use Period (EFUP) label. This product should be recycled after its environmental protection use period has expired because it may contain substances or elements as shown in the following table:

| Part Name | Hazardous Substance | | | | | |
|------------|---------------------|--------------|--------------|------------------------------|--------------------------------|---------------------------------------|
| | Lead (Pb) | Mercury (Hg) | Cadmium (Cd) | Hexavalent Chromium (Cr(VI)) | Polybrominated biphenyls (PBB) | Polybrominated diphenyl ethers (PBDE) |
| Connectors | X | 0 | 0 | 0 | 0 | 0 |

This table is prepared in accordance with the provisions of SJ/T 11364.

0: Indicates that said hazardous substance contained in all of the homogeneous materials for this part is below the limit requirement of GB/T 26572

X: Indicates that said hazardous substance contained in at least one of the homogeneous materials used for this part is above the limit requirement of GB/T 26572

The table shows where these substances may be found in this Electrical and Electronic Product.

Please refer any questions to our Product Compliance Team:

Product-Compliance@binder-connector.de

Certificate of Compliance

Issued to:

Franz Binder GmbH & Co. Elektrische Bauelemente KG
Roetelstrasse 27 Neckarsulm 74172
Germany

This certificate confirms that representative samples of:

CYJV2 - Cable Assemblies and Fittings for Industrial Control and Signal Distribution - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 2238, Edition 3, Issue Date 2018-10-02, Revision Date 2024-03-12

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



David Piecuch
UL Mark Certification Program Owner



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L302391-0812113-03111202-3
Report reference E302391-20211130
Date 2024-11-25

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

| Model | Product Description |
|--|----------------------|
| Inlet, "Series 707", Cat. No(s). 76 followed by suffixes: 70, 80, 81, 82 or 83, followed by 05, followed by 0, 1, 2 or 3, followed by 0 or 1, followed by 11, 16 or 17 followed by 00 or any two digits, followed by 0 thru 6, followed by 03 or 04 followed by any other 4 digits. | Inlet, "Series 707" |
| Cat. No(s). 76 followed by suffixes: 80, 81, 82 or 83, followed by 06, followed by 0, 1, 2 or 3, followed by 0 or 1, followed by 11, 16 or 17 followed by 00 or any two digits, followed by 0 thru 6, followed by 03 or 04 followed by any other 4 digits. | Outlet, "Series 707" |
| Inlet, "Series 707", Cat. No(s). 86 followed by suffixes:, 70, 80, 81, 82 or 83, followed by 05, followed by 0, 1, 2 or 3, followed by 0 or 1, followed by 00, 02, 11, 16 or 17 followed by 00 or any two digits, followed by 0 thru 6, followed by 03 or 04 followed by any other 4 digits. | Inlet, "Series 707" |
| Cat. No(s). 86 followed by suffixes: 80, 81, 82 or 83, followed by 05, followed by 0, 1, 2 or 3, followed by 0 or 1, followed by 00, followed by 00 or any two digits, followed by 0 thru 6, followed by 03 or 04 followed by any other 4 digits. | Inlet, "Series 707" |
| Cat. No(s). 86 followed by suffixes: 80, 81, 82 or 83, followed by 05, followed by 0, 1, 2 or 3, followed by 0 or 1, followed by 02, followed by 00 or any two digits, followed by 0 thru 6, followed by 03 or 04 followed by any other 4 digits. | Inlet, "Series 707" |
| Cat. No(s). 86 followed by suffixes: 80, 81, 82 or 83, followed by 06, followed by 0, 1, 2 or 3, followed by 0 or 1, followed by 00, followed by 00 or any two digits, followed by 0 thru 6, followed by 03 or 04 followed by any other 4 digits. | Outlet, "Series 707" |
| Cat. No(s). 86 followed by suffixes: 80, 81, 82 or 83, followed by 06, followed by 0, 1, 2 or 3, followed by 0 or 1, followed by 02, followed by 00 or any two digits, followed by 0 thru 6, followed by 03 or 04 followed by any other 4 digits. | Outlet, "Series 707" |



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Issued to:

Franz Binder GmbH & Co. Elektrische Bauelemente KG
Roetelstrasse 27 Neckarsulm 74172
Germany

This certificate confirms that representative samples of:

CYJV8 - Cable Assemblies and Fittings for Industrial Control and Signal Distribution Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CSA C22.2 No. 182.3, 2nd Ed., Issue Date: 2016-07, Revision Date: 2021-5

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



David Piecuch
UL Mark Certification Program Owner



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L302391-0815113-03111202-3
Report reference E302391-20211130
Date 2024-11-25

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

| Model | Product Description |
|--|----------------------|
| Inlet, "Series 707", Cat. No(s). 76 followed by suffixes: 70, 80, 81, 82 or 83, followed by 05, followed by 0, 1, 2 or 3, followed by 0 or 1, followed by 11, 16 or 17 followed by 00 or any two digits, followed by 0 thru 6, followed by 03 or 04 followed by any other 4 digits. | Inlet, "Series 707" |
| Cat. No(s). 76 followed by suffixes: 80, 81, 82 or 83, followed by 06, followed by 0, 1, 2 or 3, followed by 0 or 1, followed by 11, 16 or 17 followed by 00 or any two digits, followed by 0 thru 6, followed by 03 or 04 followed by any other 4 digits. | Outlet, "Series 707" |
| Inlet, "Series 707", Cat. No(s). 86 followed by suffixes:, 70, 80, 81, 82 or 83, followed by 05, followed by 0, 1, 2 or 3, followed by 0 or 1, followed by 00, 02, 11, 16 or 17 followed by 00 or any two digits, followed by 0 thru 6, followed by 03 or 04 followed by any other 4 digits. | Inlet, "Series 707" |
| Cat. No(s). 86 followed by suffixes: 80, 81, 82 or 83, followed by 05, followed by 0, 1, 2 or 3, followed by 0 or 1, followed by 00, followed by 00 or any two digits, followed by 0 thru 6, followed by 03 or 04 followed by any other 4 digits. | Inlet, "Series 707" |
| Cat. No(s). 86 followed by suffixes: 80, 81, 82 or 83, followed by 05, followed by 0, 1, 2 or 3, followed by 0 or 1, followed by 02, followed by 00 or any two digits, followed by 0 thru 6, followed by 03 or 04 followed by any other 4 digits. | Inlet, "Series 707" |
| Cat. No(s). 86 followed by suffixes: 80, 81, 82 or 83, followed by 06, followed by 0, 1, 2 or 3, followed by 0 or 1, followed by 00, followed by 00 or any two digits, followed by 0 thru 6, followed by 03 or 04 followed by any other 4 digits. | Outlet, "Series 707" |
| Cat. No(s). 86 followed by suffixes: 80, 81, 82 or 83, followed by 06, followed by 0, 1, 2 or 3, followed by 0 or 1, followed by 02, followed by 00 or any two digits, followed by 0 thru 6, followed by 03 or 04 followed by any other 4 digits. | Outlet, "Series 707" |



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.