

Max-Kleen™ Tri-V™ Heavy-Duty Degreaser

Product# VVV2279, VVV179, VVV579, VVV5579

Product Description

Max-Kleen Tri-V is ideal for removal of all types of soils including oxidized oil and grease from electronic / electrical motors and relays. Tri-V nPB replacement chemistry is a novel new chemistry that does not contain any n-propyl bromide, TCE, any hazardous air pollutants or ozone depleting compounds. It is the ideal solvent for most electronic / electrical applications. This extra-strength cleaner evaporates quickly without leaving a residue behind.

- Quickly removes all types of tough soils including oxidized oil and grease
- Best product for electrical applications
- Dielectric strength of >30 kV (liquid)
- Does not contain n-propyl bromide, trichloroethylene, perchloroethylene, HAP's, or any ozone depleting compounds
- Nonflammable, no flash point
- Stabilized for metals such as aluminum, magnesium, titanium, and brass
- Noncorrosive, safe for sensitive metals
- Leaves no residue

Typical Applications

Max-Kleen Tri-V can be used for all repair, maintenance, and manufacturing applications including:

- Removes grease, oil, lubricants, wax and tar
- Cleans contacts, relays and switches, circuit breakers and fuse blocks
- All repair and maintenance cleaning including: controls, conveyors and gear drives controllers
- Cleans electric motors and logic controllers



Typical Product Data and Physical Properties

Boiling Point:	Aerosol:	Liquid:
	118°F / 48°C	108°F / 42°C
Solubility in Water:	Negligible	
Specific Gravity:	Aerosol:	Liquid:
	1.22	1.27
Vapor Pressure @68°F	Aerosol:	Liquid:
	175 mm Hg	405mmHg
Appearance	Clear, colorless liquid	
Odor	Mild	
Flash Point (TCC):	None	
Evaporation Rate: (butyl acetate =1)	>1	
Dielectric Breakdown (ASTM D-877)	Aerosol:	Liquid:
	8 kV	32 kV
VOC* Content:	Aerosol:	Liquid
	CARB	73%
SCAQMD	854g/L	1138g/L
Federal	70%	90%
Kauri-Butanol (KB) Number	128	
Shelflife	Aerosol:	5 years from DOM
	Liquid:	2 years after opening
RoHS Compliant	Yes	

* Volatile Organic Compound (VOC) information is calculated on a weight basis using the VOC definition of California Air Resources Board (CARB) Consumer Product Regulations, South Coast Air Quality Management District (SCAQMD) Rule 102 and the Federal definition published in 40 CFR 51.100(s).

Max-Kleen™ Tri-V™ Heavy-Duty Degreaser

Product# VVV2279, VVV179, VVV579, VVV5579

Compatibility

Max-Kleen Tri-V is compatible with most metals. As with any solvent, compatibility with plastics should be determined on a non-critical area prior to use. Materials such as polystyrene, ABS, polycarbonate and PVC are not compatible with the cleaning solvent in Max-Kleen Tri-V.

Material	Compatibility
ABS	Non-Compatible
Buna-N	Fair
EPDM	Fair
Graphite	Excellent
HDPE	Excellent
LDPE	Good
Lexan	Poor
Neoprene	Fair
Noryl	Poor
Nylon 66	Excellent
Cross-Linked PE	Excellent
Polypropylene	Excellent
Polystyrene	Non-Compatible
PVC	Excellent
Silicone Rubber	Poor
Teflon	Excellent
Viton	Fair

Performance

Soil Removal – Vapor Degreasing

Lubrizol Corrosion Inhibitor	100% Removal
Unilube All Purpose Grease	91.3% Removal
5W30 Synthetic Oil	100% Removal
Fire Resistant Hydraulic Fluid	100% Removal
Chain Lubricant	100% Removal
Silicone Fluid	100% Removal

Soil Removal – Ultrasonic Cleaning

Lubrizol Corrosion Inhibitor	100% Removal
Unilube All Purpose Grease	100% Removal
5W30 Synthetic Oil	100% Removal
Fire Resistant Hydraulic Fluid	100% Removal
Chain Lubricant	100% Removal
Silicone Fluid	100% Removal

Usage Instructions

For industrial use only. Read SDS carefully prior to use.

For aerosol usage - Spray 4-6 inches from surface to clean. Wash parts from top to bottom, allowing the liquid to flush away dissolved soils. For precise application use attached extension tube.

For vapor degreasing or ultrasonic cleaning application, charge sump tank with solvent. For ultrasonic or soak applications, be sure to cover tank when not in use to prevent evaporation.

As with all vapor degreaser equipment and processes, observe all safety precautions, guidelines and operating rules associated with these units. Failure to do so may put operations personnel at risk. Avoid excessive vapor losses, loss of refrigeration, excessive boil sump heat, etc. Make sure all equipment is operated in accordance with the manufacturer's guidelines and instructions. If in doubt, contact your manufacturer immediately.

Soak applications - Allow the soiled article to soak in Max-Kleen Tri-V for 5 - 10 minutes, then remove and loosen any remaining soils with a Controlwipes Wipe.

Wipe applications - Wet a Controlwipes Wipe with Max-Kleen Tri-V and wipe away soils.

Availability

VVV2279	20 oz. / 567 g Aerosol
VVV179	1 gal. / 3.7 L Liquid
VVV579	5 gal. / 19 L Liquid
VVV5579	53 gal. / 200 L Liquid

Technical and Application Assistance

Chemtronics provides a technical hotline to answer your technical and application related questions.
The toll free number is: 1-800-TECH-401.

Note:

This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly. CHEMTRONICS does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

PHYSICAL PROPERTIES	Max-Klean™ Tri-Y		n-Propyl Bromide (nPB)		Trichloroethylene (TCE)		Perchloroethylene (Perc)		Methylene Chloride	
	None	125	None	125	None	129	None	90	None	136
Flash Point	None	125	None	125	None	129	None	90	None	136
KB Valu	128	24	24	24	30	30	45.7	24	24	24
Dielectric Strength (kV)	32	24	24	24	29	29	32	27	27	27
Surface Tension (dynes/cm)	32	24	24	24	29	29	32	27	27	27
Evaporation Rate (n-butyl acetate =1)	>1	0.28	0.28	0.28	4.45	4.45	1.5	7	7	7
Boiling Point	108°F / 42°C	158°F / 70°C	158°F / 70°C	158°F / 70°C	189°F / 87°C	189°F / 87°C	250°F / 121°C	104°F / 40°C	104°F / 40°C	104°F / 40°C
Specific Gravity @ 20°C	1.26	1.35	1.35	1.35	1.46	1.46	1.62	1.31	1.31	1.31
Vapor Pressure (mm Hg) @ 20°C	405	111	111	111	58	58	14	355	355	355
Heat of Vaporization (cal/g)	68	59	59	59	57.2	57.2	50.1	78.7	78.7	78.7

ENVIRONMENTAL & HEALTH REGULATORY

Ozone Depleting Potential (ODP)	0	0.016-0.019	0	0	0	0	0	0	0	0
Global Warming Potential (GWP)	Low	0.31	140	140	Negligible	Negligible	Negligible	8.7	8.7	8.7
Volatile Organic Compounds (VOC)	Yes	Yes	Yes	Yes	Exempt	Exempt	Exempt	Exempt	Exempt	Exempt
SNAP Approved	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Hazardous Air Pollutant (HAP)	No	Proposed	Proposed	Proposed	Yes	Yes	Yes	Yes	Yes	Yes
Prop 65 Chemical	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Carcinogen (or suspected)	No	Yes	Yes	Yes	Yes	Yes	Suspected	Suspected	Suspected	Suspected
Threshold Limit Value (ppm) (TLV)	200	10	25	25	25	25	25	25	25	25

MATERIAL COMPATIBILITY

	++ = Excellent	+ = Good	O = Fair	- = Poor	--- = Not Compatible
ABS	-	O	-	-	-
Buna-N	O	+	-	-	-
EPDM	O	-	-	-	-
Graphite	++	++	++	++	++
HDPE	++	++	O	O	O
LDPE	++	O	-	-	-
Lexan	-	-	-	-	-
Neoprene	O	O	-	-	-
Noryl	-	+	-	-	-
Nylon 66	+	++	O	O	O
Cross-Linked PE	+	++	++	++	++
Polypropylene	++	+	O	O	O
Polystyrene	-	--	--	--	--
PVC	+	+	-	-	-
Silicone Rubber	O	--	--	--	--
Teflon	++	++	++	++	++
Viton	+	++	++	++	++