

6		5		4		3		2		1	
										used for: LWL	
H											
G											
F											
E											
D											
C											
B											
A											
6		5		4				2		1	

Technical drawing of the SC/ST Duplex Hybrid Adapter. The drawing includes three views: a front view, a side view, and a mounting cutout view. Dimensions are provided in millimeters (mm). The front view shows a total width of 29 mm, with a central section of 12.3 mm and a side section of 3.6 mm. The side view shows a total height of 25.46 ± 0.2 mm, a central section of 6 mm, and a side section of 7 mm. The mounting cutout view shows a total width of 9.7 ± 0.3 mm, a central section of 2.2 mm, and a total height of 30.66 ± 0.1 mm. The drawing also shows the adapter's internal structure, including the housing, sleeve, and threaded inserts.

TECHNICAL DATA:

OUTER HOUSING MATERIAL: ZINC DIE CAST; NICKEL PLATED

INNER HOUSING MATERIAL: PLASTIC (UL 94 V-0)

SLEEVE: SEE TABLE

THREADED INSERTS: COPPER ALLOY; TIN PLATED

SCREWS: STEEL; NICKEL PLATED

ADAPTERS ARE SUPPLIED WITH DUST CAPS

SM/MM	Sleeve	Inner Housing Colour	Mount	Part number
Singlemode/Multimode				
SM = Singlemode	ceramic	blue	M2x6 screw	18-010380
MM = Multimode	ceramic	beige	M2x6 screw	18-010400
MM = Multimode	phosphor-bronze	beige	M2x6 screw	18-010420

Directive 2002/95/EC
"RoHS"
Compliant

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.

OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

		tolerance				scale: 2:1	
				dim. in mm		material: see technical data	
		2010	date	name		title: SC/ST DUPLEX HYBRID ADAPTER SINGLEMODE / MULTIMODE; METAL with thread	
		drawn	11.05.	Schmidt			
		appd.	16.05.	Kühle			
		norm					
		d-old					dwg no: AutoCAD 2006 DIN-A
a	Origin				18K1A748		
rev.	description	date	name				3
part no: see table							sh: 1/1