J1MAPD - 26XP Product Details

J1MAPD - 26XP
(4 - 1617118 - 8)
TE Internal Number: 4 - 1617118 - 8
Active

Military/Aerospace High Performance Relays

Not EU RoHS or ELV Compliant

Product Highlights:

- 1MAD TO -5 Relay Series
- Input Voltage = 26.5 VDC
- Contact Arrangement = 1 Form C, SPDT, 1 C/O
- Contact - Rated Current = 1 A
- Non Polarized, Monostable Coil - Magnetic System

View all Features

Add to My Part List | Request Sample | Find Similar Products | Buy Product

Quick Links

- Check Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Contact Us About This Product

Documentation & Additional Information

Product Drawings:
- None Available

Catalog Pages/Data Sheets:
- RELAY (PDF, English)

Product Specifications:
- None Available

Application Specifications:
- None Available

Instruction Sheets:
- None Available

CAD Files:
- None Available

List all Documents

Additional Information:
- Product Line Information

Related Products:
- Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:
- Series = 1MAD TO -5 Relay
- Termination Type = PC Pins

Electrical Characteristics:
- Input Voltage (VDC) = 26.5
- Contact - Rated Current (A) = 1
- Coil Polarity Protection Diode = Without
- Transistor Driver = Without
- Coil Resistance (?) = 2000
- MOSFET Driver = Without
- Coil Power Measurement = Milliwatts
- Coil - Rated Power (mW) = 351
- Actuating System = DC
- Shock = 75 G's, 6ms
- Vibration = 30G's, 10 to 3000Hz

Contact Features:
- Mounting Options = PC Board
- Enclosure Type = Hermetically Sealed

Configuration Features:
- Contact Arrangement = 1 Form C, SPDT, 1 C/O
- Coil - Magnetic System = Non Polarized, Monostable
- Coil Suppression Diode = With

Industry Standards:
- Government/Industry Qualification = Yes
- Government/Industry Part Number = M39016/23 -024P
- RoHS/ELV Compliance = Not ELV/RoHS compliant
- Lead Free Solder Processes = Not suitable for lead free processing
- Approved Standards = M39016 Qualified, P Level

Conditions for Usage:
- Temperature Range (°C) = -65 – +125

Other:
- Brand = CII

© 2011 Tyco Electronics Corporation, a TE Connectivity Ltd. company. All Rights Reserved | Privacy Policy