

DTS26W15-35SN [V001] ✓ ACTIVE

DEUTSCH | DEUTSCH 38999 Series III, DEUTSCH 38999

TE Internal #: YDTS26W15-35SNV001

37 Position Circular Connector, Cable-to-Panel, Sealable, Wire & Cable, Signal, Panel Mount, Cadmium, O.D., Aluminum 6061-T6, DEUTSCH 38999 Series III

[View on TE.com >](#)



Connectors > Circular Connectors > Standard Circular Connectors > D38999: Straight Plug, 15-35 Insert



Connector System: **Cable-to-Panel**

Connector Mounting Type: **Panel Mount**

Number of Positions: **37**

Sealable: **Yes**

Connector & Contact Terminates To: **Wire & Cable**

[All D38999: Straight Plug, 15-35 Insert \(2\)](#)

Features

Product Type Features

Connector Product Type	Connector Assembly
Assembly Type	Electrical Connector
Connector System	Cable-to-Panel
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Circular Connector Type	Plug
Shell Type	Straight Plug

Configuration Features

Keying & Polarized Position Locations	N
Factory Installed Backshell	No
Number of Positions	37
Number of Power Positions	0
Number of Signal Positions	37
Contacts Preloaded	No

Electrical Characteristics

Operating Voltage	550 VDC
-------------------	---------



Body Features

Entry Style	Rear Insertion
Environmental Protection	Yes
Environmental Protection Type	Elastomer Sealed
Fluid Type	M2-V, MIL-DTL-5624 (JP-4,JP-5), MIL-DTL-83133 (JP-8), MIL-PRF-23699, MIL-PRF-5606, MIL-PRF-7808, SEA-AMS1424 Type I, Synthetic Hydrocarbon Heat Transfer Fluid
Feedthrough Type	No
Shell Plating Material	Cadmium, O.D.
Shell Base Material	Aluminum 6061-T6
Circular Connector Insulation Material Type	Hard Dielectric/Silicone
Hermetically Sealed	No

Contact Features

Contact Quantity (Size 22D)	37
Contact Current Rating (Max)	5 A
Reverse Gender	No
Contact Layout Arrangement	15 – 35
Circular Connector Contact Type	Socket

Mechanical Attachment

Panel Mount Feature	Without
Mating Retention Type	Triple Start Threaded
Connector Mounting Type	Panel Mount
Polarization Code	N
Mating Alignment Type	Keyed
Mating Retention	With

Housing Features

Circular Connector Shell Size	15
Alignment Keyed	Clocking

Dimensions

Compatible Insulation Diameter Range	.76 – 1.37 mm [.03 – .054 in]
Assembly Length	31 mm [1.22 in]
Wire Size	28 – 22 AWG



Usage Conditions

Operating Temperature Range	-65 – 200 °C[-85 – 392 °F]
-----------------------------	----------------------------

Operation/Application

Durability Rating	500 Cycles
Circuit Application	Signal
Shielded	Yes

Packaging Features

Packaging Quantity	1
--------------------	---

Other

Position Locations Omitted	All
----------------------------	-----

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Cd (100% in 10563725794) Article Safe Usage Statements: Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 70H1-23-15-1-B
70H1-23-15-1-B



TE Part # 70H1-15-07-1-B
70H1-15-07-1-B



TE Part # 70H1-15-18-1-B
70H1-15-18-1-B



TE Part # 70H1-15-08-1-B
70H1-15-08-1-B



TE Part # 70H1-15-15-1-B
70H1-15-15-1-B



TE Part # 70H1-15-14-1-B
70H1-15-14-1-B



TE Part # EK4780-000
70H1-15-10-1-B



TE Part # 70H1-15-09-1-B
70H1-15-09-1-B



TE Part # 70H1-15-03-1-B
70H1-15-03-1-B



TE Part # CAT-D38999-DTS15G
Jam Nut: D38999, 15-35 Insert



TE Part # 70H1-15-12-1-B
70H1-15-12-1-B



TE Part # 70H1-15-05-1-B
70H1-15-05-1-B



TE Part # CAT-D38999-DTS6O
D38999: Square Flange, 15-35 insert



TE Part # 70H1-15-06-1-B
70H1-15-06-1-B

Also in the Series | **DEUTSCH 38999 Series III**



Standard Circular Connectors(497)

Also in the Series | DEUTSCH 38999



Standard Circular Connectors(497)


Customers Also Bought



TE Part #CAT-HST-RNF100-BK
RNF-100-BK Heat Shrink Tubing



TE Part #448859-000
D-1744-01



TE Part #814439-000
214A021-3-0



TE Part #621065-000
D-142-65




TE Part #53425-1
TERMINAL,PIDG PVF2 R 12-10 10



TE Part #1447009-5
SHIELD FINGER 0820 TYPE



TE Part #9-1879129-2
RN 0402 2K49 0.1% 10PPM 1K RL



TE Part #2430088-1
EMI Fan Vent 120mm



TE Part #1878643-3
M5031



Documents

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_YDTS26W15-35SNV001_99.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_YDTS26W15-35SNV001_99.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_YDTS26W15-35SNV001_99.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[DEUTSCH MIL-DTL-38999 Connectors Quick Reference Guide](#)

English