



Product Navigation

Circuit Board Indicators

Panel Mount Indicators

Solid State Lighting

Traffic Signals

Vehicle Lighting

Rail

Obstruction Lighting

Hazardous Area Lighting

Heliport Lighting

how to purchase

 sales contacts

 stock check

 search

 Product Line Search

Please select a Product Line to search.

Circuit Board Indicators

find

Part # / Text Search

Part No.:

Text Search:

search

 quick links

Dialight Corporate Video

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

Application Notes
FAQs

Dialight Ltd (UK)
Dialight Garufo
Dialight BLP
LumiDrives

Circuit Board Indicators - Through Hole Indicators

P/N# 5522333F

5 mm Lens Single Color

Description
Package Options
Product Type
Sub Product Type
Configuration
Lamp Type
Viewing
Viewing Angle
Test Current (mA)
Forward Current (mA)
LED Centerline
Polarity

5 mm Bi-Level CBI
50 Pieces Per Bag
Through Hole Indicators
with Bi-Level Housing
5 mm Lens
Single Color
Right Angle
24
20mA
20mA
3.2
Cathode Right

Absolute Maximum Ratings (Ta = 25 °)

Derating
Reverse Voltage
Solder Temp
Operating Temp
Storage Temp

from 50Â° @ 1.6 mW/Â°C
5 V
260Â° for 5 sec
-55 to +100° C
-55 to +100° C


RoHS /pB Free
view PDF

Distributor Stock Check

Check stock with our distributors now.

5522333F

check stock

Operating Characteristics

LED Position	1,2
Color	Yellow
Lamp Type	Single Color
LED Type	Super Bright
Intensity Min (mcd)	80
Intensity Typ (mcd)	140.0
Intensity Max (mcd)	
Fwd Voltage Min	
Fwd Voltage Typ	
Fwd Voltage Max	
Dom Wavelength Min (nm)	
Dom Wavelength Typ (nm)	
Dom Wavelength Max (nm)	
Power Dissipation Max (mW)	85
Backlighting	
Pitch Between Vertical	6.35
Pitch Between Horizontal	
Lum Intensity Min	
Lum Intensity Typ	
Lum Intensity Max	