



Circuit Board Indicators

Panel Mount Indicators

Solid State Lighting

Traffic Signals

Vehicle Lighting

Rail

Obstruction Lighting

Hazardous Area Lighting

Heliport Lighting

how to purchase

[sales contacts](#)
[stock check](#)
[search](#)

Product Line Search

Please select a Product Line to search.

Circuit Board Indicators

find

Part # / Text Search

Part No.:

Text Search:

search

quick links

Dialight Corporate Video

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

Application Notes
FAQs

Dialight Ltd (UK)
Dialight Garufo
Dialight BLP
LumiDrives

Circuit Board Indicators - Through Hole Indicators

P/N# 5710101F

2 mm Lens


Description
Package Options
Product Type
Sub Product Type
Configuration
Viewing
Viewing Angle
Test Current (mA)

2 mm Bi-Level CBI X-R
50 Pieces Per Bag
Through Hole Indicators
with Bi-Level Housing
2 mm Lens
Right Angle
70
10mA

Absolute Maximum Ratings (Ta = 25 °)

Solder Temp
Operating Temp
Storage Temp

260Å° for 5 sec
-40 to +85° C
-40 to +85° C



Operating Characteristics

LED Position	Found in position(s): 1	Found in position(s): 2
Color	Blank	Red
Lamp Type	Single Color	Single Color
LED Type		High Efficiency
Intensity Min (mcd)		8.0
Intensity Typ (mcd)		15.0
Intensity Max (mcd)		
Fwd Voltage Min		
Fwd Voltage Typ		
Fwd Voltage Max		
Dom Wavelength Min (nm)		625
Dom Wavelength Typ (nm)		
Dom Wavelength Max (nm)		
Power Dissipation Max (mW)		105
Backlighting		
Pitch Between Vertical		
Pitch Between Horizontal		
Lum Intensity Min		
Lum Intensity Typ		
Lum Intensity Max		

Distributor Stock Check

Check stock with our distributors now.

5710101F

[check stock](#)