

| | | | | |
|---|----------|----|-----|----------------------|
| Product designation | | | | Rotary cam switches |
| Product type designation | | | | GN25 |
| General characteristics | | | | |
| Switching diagram | | | | 10 |
| N° of elements | | | | 2 |
| Options | | | | IEC IP65 front plate |
| Contact characteristics | | | | |
| Rated insulation voltage U_i | IEC/EN | V | 690 | |
| | UL/CSA | V | 600 | |
| Rated impulse withstand voltage U_{imp} | | kV | 6 | |
| Conventional free air thermal current I_{th} | IEC/EN | A | 25 | |
| | UL/CSA | A | 30 | |
| Rated operational voltage | | V | 480 | |
| Maximum fuse size for short-circuit protection I_n (gG) | 10kA | A | 25 | |
| | 25kA | A | 25 | |
| Rated short time current I_{cw} | 1s | A | 400 | |
| Operational current I_e IEC/EN | | | | |
| AC1/AC21A | | A | 25 | |
| AC15 | 110V | A | 16 | |
| | 220/230V | A | 12 | |
| | 380/400V | A | 8 | |
| | 660/690V | A | 2 | |
| Rated operational power in AC | | | | |
| Three-phase AC3 | 220/230V | kW | 5.5 | |
| | 500/690V | kW | 7.5 | |
| Single-phase AC3 | 110V | kW | 1.5 | |
| | 220/230V | kW | 3 | |
| | 380/440V | kW | 5.5 | |
| Three-phase AC23A | 220/230V | kW | 6.5 | |
| | 380/440V | kW | 11 | |
| | 500/690V | kW | 11 | |
| Single-phase AC23A | 110V | kW | 1.5 | |
| | 220/230V | kW | 3.7 | |
| | 380/440V | kW | 5.5 | |
| Rated operational current in DC | | | | |
| DC21A | 48V | A | 25 | |
| | 60V | A | 25 | |
| | 110V | A | 4 | |
| | 220V | A | 0.7 | |
| DC23A (poles in series) | | | | |

| | | |
|------|---|--------|
| 24V | A | 25 (1) |
| 48V | A | 25 (2) |
| 60V | A | 25 (3) |
| 110V | A | 12 (3) |
| 220V | A | 10 (4) |

DC13

| | | |
|------|---|-----|
| 24V | A | 25 |
| 48V | A | 20 |
| 60V | A | 16 |
| 110V | A | 1.5 |
| 220V | A | 0.4 |

Mechanical features

Terminals screw M3.5

Tightening torque for terminals max Nm 0.8

Conductor size

AWG - Rigid cable

| | | |
|-----|-----|----|
| min | AWG | 20 |
| Max | AWG | 10 |

AWG - Flexible cable

| | | |
|-----|-----|----|
| min | AWG | 20 |
| Max | AWG | 12 |

Conductor size (IEC) - Flexible cable

| | | |
|-----|-----------------|-----|
| min | mm ² | 0.5 |
| Max | mm ² | 4 |

Conductor size (IEC) - Rigid cable

| | | |
|-----|-----------------|-----|
| min | mm ² | 0.5 |
| Max | mm ² | 4 |

Mechanical life cycles 5x10⁶

UL technical data

Motor power for direct-on-line control

for three-phase motor

| | | |
|------|----|----|
| 480V | HP | 10 |
|------|----|----|

Ambient conditions

Temperature

Operating temperature

| | | |
|-----|----|-----|
| min | °C | -25 |
| max | °C | +55 |

Storage temperature

| | | |
|-----|----|-----|
| min | °C | -40 |
| max | °C | +70 |

Resistance & Protection

Frontal IP degree IP40

Terminals IP degree IP00

ETIM classification

ETIM 8.0

EC001029 -
Selector switch,
complete