

Product designation	Automatic transfer switch controller for 3 power sources and two tie-breakers, three phase control, with LCD display, built-in RS485, expandable		
Product type designation	ATL900		
General characteristics			
Number of controlled power sources	Nr.	3	
Number of tie-breaker controlled	Nr.	2	
Display	Backlit LCD graphic display 128x112 pixel		
Languages	Nr.	8	
Expandability	3 expansion slots for EXP... Modules		
AC Power supply			
Rated supply voltage AC	VAC	100...240	
Operating supply voltage range AC	VAC	90...264	
Rated frequency	Hz	50/60	
Operating frequency range	Hz	45...66	
Immunity time for microbreakings	110VAC	ms	≤40
	220VAC	ms	≤200
Immunity time for microbreakings (with EXP expansions)	110VAC	ms	≤20
	220VAC	ms	≤100
Power consumption AC (Max)	VA	16.5	
DC Power supply			
Rated supply voltage DC	VDC	12-24-48	
Operating supply voltage range DC	VDC	7.5...57.6	
Current consumption Max	mA	510mA at 12VDC, 260mA at 24VDC, 135mA at 48VDC	
Maximum power consumption / dissipation	W	6.5	
Voltage inputs			
Maximum rated voltage Ue	100...600VAC L-L (346VAC L-N)		
Measurement range	V	50...720VAC L-L (415VAC L-N)	
Frequency range	Hz	45...66Hz - 360...440Hz	
Measurement method	True root mean square (TRMS)		
Input impedance	phase-phase	kΩ	>1.10MΩ
	phase-neutral	kΩ	>0.55MΩ
Measuring accuracy	±0.25% f.s. ±1 digit		

Wiring mode		Single-phase, two-phase, three-phase line with or without neutral and balanced three-phase system
Current inputs		
Rated current (Ie)	A	1A~ or 5A~
Measurement range		for scale 5A: 0.02 - 6A~ for scale 1A: 0.02 - 1.2A~
Type of input		Shunt supplied by external current transformer (low voltage) 5A max
Measurement method		True root mean square (TRMS)
Overload capacity		1.2 Ie
Overload peak	A	50A for 1 second
Burden per phase	W	<0.6VA
Digital inputs		
Number of digital input	Nr.	12
Type of digital input		Negative
Digital current inputs	mA	≤8
Low input signal	VDC	≤2.2
High input signal	VDC	≥3.4
Input signal delay	ms	≥50
Calendar clock		
Backup reserve power		Backup capacitor
Operating without power voltage		14 days approximately
Relay outputs		
Number of relay output	Nr.	10
Contact arrangement		6 x 1NO-SPST + 4 x C/O-SPDT
Electrical life	cycles	105
Mechanical life	cycles	107
Static Outputs		
Number of static output		1 (OUT8)
Static output type		NO
Operating voltage	V	10...30
Maximum current	mA	50
Interface		
NFC interf.		Yes
Front optical USB communication port		Yes, with CX01 USB dongle (optional)
Front optical Wi-Fi communication port		Yes, with CX02 Wi-Fi dongle (optional)
USB communication		EXP1010 (optional)

RS232 communication	EXP1011 (optional)
RS485 communication	Built-in or EXP1012 (optional)
Ethernet communication	EXP1013 (optional)
Profibus communication	EXP1014 (optional)
Communication via Modem	EXP1015 (optional)

Functions

Number of tie breakers that can be managed	2
Programmable source type	Yes
Closed transition	Yes
Non-priority load management	Yes
Switching management with power thresholds	Yes
PLC logic	Yes
Timer	Yes
System layout available on display	14
Custom system layouts	Yes
User alarms	Yes
Limits	Yes
Event logging	250
Real time clock with backup reserve energy	Yes
Acoustic alarms	Yes
Analogue inputs	EXP1004 (optional)
Analogue outputs	EXP1005 (optional)
Accessory for alarm remoting	RGKRR (optional)

Ambient conditions

Temperature			
Operating temperature			
	min	°C	-30
	max	°C	+70
Storage temperature			
	min	°C	-30
	max	°C	+80
Relative humidity		%	<80%
Maximum Pollution degree			2
Overvoltage category			3
Measurement category			III
Climatic sequence			Z/ABDM (IEC/EN 60068-2-61)
Shock resistance			15g (IEC/EN 60068-2-27)
Vibration resistance			0.7g (IEC/EN 60058-2-6)

Housing

Execution	Flush mount
Material	Polycarbonate

Mounting		Flush mount - panel cut-out 220x160 mm
Degree of protection		IP65 on front, IP20 on terminals
Dimensions (W x H x D)	mm	240 x 180 x 43.9
Weight	g	1800

Dimensions

Wiring diagrams

Certifications and compliance

Compliance

- CSA C22.2 n° 14
- IEC/EN 60947-1
- IEC/EN 60947-6-1
- IEC/EN 61000-6-2
- IEC/EN 61000-6-4
- IEC/EN 61010-1
- IEC/EN 61010-2
- UL508

Certificates

- cULus
- EAC
- RCM

ETIM classification

ETIM 8.0	EC000236 - PLC CPU-module
----------	---------------------------