

Product designation	Variable speed drives		
Product type designation	VLA1		
<b>General characteristics</b>			
Rated power supply voltage	Single phase 200...240VAC 50/60Hz		
Rated output voltage	VAC	Three-phase 0...240VAC 0- 599Hz	
Rated output current	A	2.4	
Rated output power	kW	0.4	
Rated output power	HP	0.5	
EMC filter	Built-in EMC suppressor cat. C2		
Communication port	No		
<b>Technical features</b>			
Input type	Single phase		
Rated mains voltage	VAC	200...240	
Operating mains voltage range	VAC	170...264	
Rated mains frequency	Hz	50/60	
Operating mains frequency range	Hz	45...65	
Rated mains current without mains choke	5.7		
Rated mains current with mains choke	4.8		
Output type	three-phase		
Output voltage range	VAC	0...240	
Output frequency range	Hz	0...599	
Current overload	%/s	150% for 60s, 200% for 3s	
Power loss	20W		
Brake chopper	No		
Switching frequency	2...16kHz		
Max motor cable length	Shielded		
	Without EMC category	m	50
	Category C2	m	15
<b>Functions</b>			
Motor control modes	V/f linear, quadratic torque, sensorless vector control, ECO mode		

Speed reference signals	External potentiometer 0...10kΩ Voltage signals: 0...10VDC Current signals: 0/4...20mA Buttons on front keyboard Door-mount installation kit 15 preset speeds via digital inputs Motor potentiometer
3-wire control	Yes
S-shape curves	Yes
Slip compensation	Yes
Flying restart	Yes
Access to DC bus	No
DC braking	Yes
DC injection at start	Yes
PID control	Yes, with sleep and rinse function
Sequencer (programmable frequency/time cycles)	Yes
Preset speeds	Yes
Motorpotentiometer	Yes
Different parameter configuration sets	Yes
Parameters changeover function	Yes
Favorite parameters menu	Yes
Autotuning	No
Safe torque Off (STO) safety function	No
PTC probe input	No
Protections	Overcurrent Output short circuit and earth/ground leakage Overvoltage Undervoltage Phase loss Motor heat overload (i2t) Overspeed Speed reverse
Special funct.	Multi-pump PID control (1 main pump frequency regulated + 2 auxiliary pumps activated in direct mode in case of necessity)

### Input and Output

Number of digital input	Nr.	5
Digital input type		Selectable PNP or NPN logic
Number of digital output	Nr.	2

Digital output arrangement		1 relay output with changeover contact (C/O-SPDT) + 1 digital output
Output contacts ratings		Relay output: 3A 250VAC Digital output: 100mA max 30VDC
Number of analog input	Nr.	2
Analog input type		Analog input 1: configurable 0/2...10VDC, 0...5VDC, 0/4...20mA Analog input 2: configurable 0/2...10VDC or 0...5VDC
Number of analog output	Nr.	1
Analog output type		configurable as 0...10VDC, 0...5VDC, 2...10VDC, 0/4...20mA

#### Ambient conditions

##### Temperature

##### Operating temperature

min	°C	-10
max	°C	+55
Current derating		2.5%/°C over 40°C

##### Storage temperature

min	°C	-25
max	°C	+60

Relative humidity		%	5...95% (with no condensing)
Max altitude		m	4000m (over 1000m derate the rated current by 5%/1000m)
Maximum Pollution degree			2
Overvoltage category			III up to 2000m altitude (II above 2000m)

#### Housing

Installation position			Vertical
IP degree of protection			IP20
Dimensions (W x H x D)		mm	60 x 183 x 130
Weight		Kg	0.75

#### Dimensions

#### Wiring diagrams

#### Certifications and compliance

##### Compliance

CSA 22.2 No. 274

---

EN 61800-5-1

---

UL61800-5-1

Certificates

---

cULus

---

EAC

---

RCM

ETIM classification

ETIM 8.0

EC001857 -  
Frequency  
converter =< 1 kV