

# Product data sheet

Specifications



Relay, SE Relays, solid state, SPST, 3A, 24...140 VAC, 6...30/32 VDC Uc, triac, printed circuit board, screw termin, inch

70S2-05-B-03-V

! Discontinued

! Discontinued on: Aug 7, 2023

**Product availability: Non-Stock - Not normally stocked in distribution facility**

## Main

Range	Legacy
Product Type	Solid state relay
maximum output current	3 A AC
Mounting Support	Printed circuit boards
Network Number of Phases	1 phase
Output Voltage	24...140 V AC

## Complementary

Holding Current	75 mA
Input Current Limits	1...6 mA at 6...30 V DC typical
Switch Function	SPST
Contacts Type and Composition	NO
Protection Type	Reverse polarity 3 V DC control
Connections Terminals	solder terminal
Switching Voltage	1 V DC tripping
Switching Device	Triac output Zero voltage switching
Maximum Peak Voltage	400 V
Surge Current	60 A 1 cycle 19 A 60 cycles
Must Release Voltage	1 V
Voltage Drop	<1.6 V on-state AC
Thermal Resistance	25 °C/W
Leakage Current	6 mA at off-state
DV/dt	300 V/ms off-state at maximum rated voltage
Dielectric Strength	3750 V minimum
Height	1.02 in (26.0 mm)
Width	0.37 in (9.42 mm)
Depth	1.2 in (31.2 mm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

Product Weight	1.2 oz (35 g)
----------------	---------------

---

## Environment

---

Product Certifications	UL Recognized CSA CE
------------------------	----------------------------

---

Ambient Air Temperature for Operation	-40...185 °F (-40...85 °C)
---------------------------------------	----------------------------

---

Ambient Air Temperature for Storage	-40...257 °F (-40...125 °C)
-------------------------------------	-----------------------------

---

## Ordering and shipping details

---

Category	US10CP221127
----------	--------------

---

Discount Schedule	0CP2
-------------------	------

---

GTIN	3606480278594
------	---------------

---

Returnability	No
---------------	----

---

Country of origin	CN
-------------------	----

---

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	1.70 in (4.33 cm)
------------------	-------------------

---

Package 1 Width	0.40 in (1.02 cm)
-----------------	-------------------

---

Package 1 Length	1.22 in (3.11 cm)
------------------	-------------------

---

Package 1 Weight	0.9 oz (25.0 g)
------------------	-----------------

---

Unit Type of Package 2	BB1
------------------------	-----

---

Number of Units in Package 2	100
------------------------------	-----

---

Package 2 Height	3.35 in (8.5 cm)
------------------	------------------

---

Package 2 Width	4.33 in (11.0 cm)
-----------------	-------------------

---

Package 2 Length	8.86 in (22.5 cm)
------------------	-------------------

---

Package 2 Weight	5.64 lb(US) (2.56 kg)
------------------	-----------------------

---

Unit Type of Package 3	CAR
------------------------	-----

---

Number of Units in Package 3	1000
------------------------------	------

---

Package 3 Height	12.40 in (31.5 cm)
------------------	--------------------

---

Package 3 Width	11.61 in (29.5 cm)
-----------------	--------------------

---

Package 3 Length	16.93 in (43.0 cm)
------------------	--------------------

---

Package 3 Weight	58.2 lb(US) (26.4 kg)
------------------	-----------------------

---


## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.


[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

 <b>Materials and Substances</b>	
Packaging without single use plastic	Yes
<a href="#">EU RoHS Directive</a>	Pro-active compliance (Product out of EU RoHS legal scope)
California proposition 65	<b>WARNING:</b> This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

### Use Again

 <b>Repack and remanufacture</b>	
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Connections and Schema

Connections and Wiring Diagrams

---

