

Product data sheet

Specifications



Time delay relay, SE Relays, 4PDT, 5A, 24 VAC, 100 ms to 100 hours, 7 time scales, on-delay function, socket compatible

TDR782XDXA-24A

⚠ Discontinued

⚠ Discontinued on: Aug 7, 2023

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product Range	Legacy
Product or Component Type	Time delay relay
Switch Function	4PDT
Contacts Material	Silver alloy contacts
Time Delay Type	A
Rated Supply Voltage	24 V AC 50...60 Hz

Complementary

Time Delay Range	100 ms...1 s 1...10 s 0.1...1 min 1...10 min 0.1...1 h 1...10 h 10...100 h
Control Type	Dial front
Voltage Range	0.85...1.15 Un 0.85...1.15 Un 0.85...1.15 Un 0.85...1.15 Un 0.85...1.15 Un 0.85...1.15 Un 0.85...1.15 Un 0.85...1.15 Un 0.85...1.15 Un 0.85...1.15 Un 0.85...1.15 Un
Nominal Output Current	3 A
Local Signalling	1 LED amber output status 1 LED green input status
Repeat Accuracy	+/- 0.5 % - 5...5 %
Temperature Drift	+/- 0.05 %/°C
Reset Time	50 ms maximum
Power Consumption in VA	1.7 VA 24 V
Electrical Durability	100000 cycles
Mechanical Durability	10000000 cycles

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Mounting Support	Socket
Height	2.3 in (59.4 mm)
Width	0.8 in (21 mm)
Depth	1.06 in (27 mm)
Product Weight	1.8 oz (50 g)

Environment

Dielectric Strength	2000 V between input and output
Standards	IEC 61810-1
Product Certifications	CSA cURus
Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C)
Ambient Air Temperature for Operation	-4...140 °F (-20...60 °C)
IP Degree of Protection	IP50 IEC 60529 enclosure)

Ordering and shipping details

Category	US10CP221127
Discount Schedule	0CP2
GTIN	3606480283048
Returnability	No
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.06 in (2.7 cm)
Package 1 Width	0.83 in (2.1 cm)
Package 1 Length	2.71 in (6.88 cm)
Package 1 Weight	1.5 oz (43 g)
Unit Type of Package 2	S01
Number of Units in Package 2	48
Package 2 Height	5.91 in (15 cm)
Package 2 Width	5.91 in (15 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	905.8 oz (25680 g)
Unit Type of Package 3	PAL
Number of Units in Package 3	1536
Package 3 Height	30.31 in (77 cm)
Package 3 Width	23.62 in (60 cm)
Package 3 Length	31.50 in (80 cm)
Package 3 Weight	28986.2 oz (821760 g)



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging without single use plastic

Yes

[EU RoHS Directive](#)

Pro-active compliance (Product out of EU RoHS legal scope)

SCIP Number

1b9c3411-e0e2-4832-adc7-e6e2a8e06cab

California proposition 65

WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov


Use Again

Repack and remanufacture

Circularity Profile

No need of specific recycling operations


WEEE

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Dimensions Drawings


Approximate Dimensions

**NOTE: Terminal size is 0.105 x 0.020
(2.68 x 0.508)**



**14 TERMINAL SQUARE
BASE 4PDT (ON DELAY)**

Approximate Dimensions



Connections and Schema

Connections and Wiring Diagrams

