



Part Number : [2065600300](#)
Product Description : 1558MHz-1610MHz GNSS
Flex Antenna, 300.00mm Cable Length, Compatible
with U.FL / I-PEX MHF Connectors
Series Number : 206560
Status : Active
Product Category : Antennas



Documents & Resources

Drawings

- [2065600300_sd.pdf](#)
- [2065600050-001.pdf](#)

3D Models and Design Files

- [STEP AP242](#)
- [SOLIDWORKS](#)
- [Creo](#)

Specifications

- [2065600050-AS.pdf](#)
- [2065600050-PS.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	 per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2025)4165-DC (25 June 2025)
EU RoHS	Compliant per EU 2015/863

- [Compliance Statements](#)
- EU RoHS

- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

Part Details

General

Status	Active
Category	Antennas
Series	206560
Description	1558MHz-1610MHz GNSS Flex Antenna, 300.00mm Cable Length, Compatible with U.FL / I-PEX MHF Connectors
Component Type	Flexible Antenna with Cable
Function	Signal
Product Name	1558MHz-1610MHz GNSS Flexible
Protocol	BeiDou, GLONASS, GPS
Type	GNSS Antenna, Internal
UPC	191128769150

Electrical

Band#1 F_End (MHz)	1564
Band#1 F_Start (MHz)	1558
Band#2 F_End (MHz)	1578
Band#2 F_Start (MHz)	1572
Band#3 F_End (MHz)	1605
Band#3 F_Start (MHz)	1599
Electrical Connectivity	Cable

Peak Gain (dBi)	0.5 @ 1561 MHz, 0.5 @ 1575 MHz, 0.9 @ 1602 MHz
Return Loss - S11 (dB)	< -8
Total Efficiency	>64% @ 1561 MHz, >64% @ 1575 MHz, >65% @ 1602 MHz

Physical

Cable Length	300.00mm
Length	40.40mm
Mounting Style	Adhesive
Net Weight	1.001/g
Packaging Type	PET Film
Polarization	Linear
Radiation Pattern	Omnidirectional
Thickness	0.10mm
Width	15.40mm

Mates With / Use With

Mates with Part(s)

Description	Part Number
MCRF Jack, Straight, PCB Receptacle, Surface Mount, 1.25mm Mounted Height, 50 Ohms	<u>734120110</u>