



Part Number : [755685140](#)

Series Number : 75568

Status : Active - Proprietary

Product Category : Board-to-Board Connectors



Drawings

[PK-46081-100-001.pdf](#)

Specifications

[PS-75431-999-001.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Compliant with Exemption 33; 44; 34
China RoHS	 per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2025)6375-DC (05 Nov 2025)
EU RoHS	Compliant per EU 2015/863

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

Part Details

General

Status	Active - Proprietary
Category	Board-to-Board Connectors
Series	75568
Description	EXTreme PowerMass Signal Module, Plug, Right-Angle, 40 Circuits, Short Pin
Application	Board-to-Board, Signal
Component Type	PCB Header, Plug
Product Name	EXTreme PowerMass
UPC	800756929781

Agency

CSA	LR19980
UL	E29179

Electrical

Current - Maximum per Contact	3.0A
Voltage - Maximum	50V

Physical

Breakaway	No
Circuits (Loaded)	40
Circuits (maximum)	40
First Mate / Last Break	Yes
Flammability	94V-0
Glow-Wire Capable	No
Guide to Mating Part	No
Keying to Mating Part	None
Lock to Mating Part	None
Material - Plating Mating	Gold

Material - Plating Termination	Tin
Net Weight	17.425/g
Number of Rows	8
Orientation	Right Angle
Packaging Type	Tray
PCB Locator	No
PCB Retention	None
PCB Thickness - Recommended	2.40mm
PC Tail Length	3.07mm
Pitch - Mating Interface	2.50mm
Pitch - Termination Interface	2.50mm
Plating min - Mating	0.762µm
Plating min - Termination	2.540µm
Polarized to Mating Part	No
Polarized to PCB	No
(p)ower-(s)ignal Configuration	40s - 0p
Shrouded	Closed Ends
Stackable	No
Termination Interface Style	Through Hole

Mates With / Use With

Mates with Part(s)

Description	Part Number
EXTreme PowerMass Signal Module, Receptacle, 40 Circuits, Tin (Sn) Tail	<u>755486040</u>