


# V19 SERIES

32349182

Issue C

## MICRO SWITCH Technology



### APPLICATIONS



#### Presence Detection

Ensures door latching and safe operation



#### Float Switch

On/off power to stop overflow conditions



#### Flow Switch

Enables safe and efficient water usage



#### Power Switch

Reliable system control for motors, pumps, fans



#### Operator Controls

Interface control for system auxiliary functions

### VALUE PROPOSITION

The V19, Honeywell's unsealed MICRO SWITCH family provides a cost-conscious switch solution to assist in hitting overall system-level cost and design goals in high volume applications. The V19 switch provides a fully certified, reliable, and repeatable solution over the lifetime of the product. RAST 2.5, 5, and 7 termination styles available for automated manufacturing requirements (white goods).

V19 FEATURES	V19 BENEFITS	OUR VALUE
5 A & 16 A	Electrical ratings for design flexibility in one industry standard package size	Competitive cross references available
> 1M mechanical operations	Globally certified for reliable, repeatable actuation for life	Snap-spring mechanism with more than 80 years of MICRO SWITCH service
UL/CSA, cUL, ENEC, CQC	Identical system designs for platform applications worldwide	Certifications enable global design acceptance and cost savings in agency approvals
Cadmium-free contacts	RoHS 3, REACH and CalProp 65 compliant	
RAST 2.5 termination and housing	Enables IDT termination for automated machinery builds on signal-level and control circuits	Combined terminal and housing construction enables agency certification (UL94V-0 & IEC 60335-1) and material cost savings

## MICRO SWITCH, V19 SERIES

Unless otherwise stated, all characteristic measurements tested according to UL, EN, and IEC standards and conditions. Parameters and acceptance criteria validated and confirmed in a certified lab environment. Technical details available upon request.

**TABLE 1. PERFORMANCE SPECIFICATIONS**

CHARACTERISTIC	MEASURE
Circuitry	SPDT, SPNO, SPNC
Operating force	0,15 N to 3,92 N [15 g to 400 g]
Termination	quick connect; 6,35 mm x 0,80 mm [0.250 in x 0.032 in] quick connect 4,80 mm x 0,50 mm [0.187 in x 0.020 in] RAST-5 250#; RAST-7 250#; RAST-2.5 straight PCB
Actuators	pin plunger, integral lever options
Agency certification	ENEC, CQC, UL, cUL
Operating temperature (manufacturer specified)	code S: -25°C to 85°C [-13°F to 185°F] code T: -25°C to 125°C [-13°F to 257°F]
Humidity	validated to 240 hours at 40°C [40°F], 95 %RH
Mechanical life (cycles)	1 million cycles @ 60 cycles/minute max.
Ingress protection rating	IP40 per IEC 60529
Vibration resistance	10 Hz to 55 Hz, displacement 1,5 mm (peak-to-peak); no contact separation > 1 millisecond
Shock resistance	destruction: 500 m/s <sup>2</sup> (50 g max.); switch is functional after test malfunction: 100 m/s <sup>2</sup> (10 g max.); no contact separation > 1 millisecond
Switch resistance	50 mΩ max. for operating force >50; 100 mΩ max. for operating force ≤50
Dielectric strength	1000 Vac (RMS) for 1 minute; leakage current ≤0.5 mA between open contacts 1500 Vac (RMS) for 1 minute, leakage current ≤0.5 mA between live parts and ground
Insulation resistance	min. 100 mΩ (500 Vdc for one minute)
Contact material	cadmium-free silver alloy
Housing material	PBT thermoplastic polyester
Actuating button material	phenolic
Auxiliary actuator material	stainless steel
Common terminal material	brass
NO/NC terminal material	brass
Moving blade	silver-plated brass
Operating speed	0,3 mm/s to 1000 mm/s (pin plunger)
Operating frequency	60 CPM mechanical, 25 CPM electrical
Average unit weight	7.17g
Packaging dimensions/weight	505 mm x 310 mm x 225 mm/1900 g

# MICRO SWITCH, V19 SERIES

**TABLE 2. ELECTRICAL SPECIFICATIONS**

RATING/NOMENCLATURE CODE	UL/CUL (CUL 61058-1, FILE 12252) AMERICAS	ENEC (IEC 61058-1) EUROPE CQC (GB15092-1) ASIA-PACIFIC
05	5 GPA 125/250 Vac; 6 GPA 125/250 Vac 1/10 HP 125/250 Vac 0.4 RA 125 Vdc; 0.3 RA 250 Vdc 10,000 cycles	5 (2.5) A 125/250 Vac, 6 (2.5) A 125/250 Vac 0.4 A 125 Vdc, 0.3 A 250 Vdc 10,000 cycles
16	16 GPA 125/250 Vac 1/2 HP 125/250 Vac 0.6 RA 125 Vdc; 0.3 RA 250 Vdc 10,000 cycles	16 (4) A 250 Vac 0.6 A 125 Vdc; 0.3 A 250 Vdc 10,000 cycles

- RA = Resistive Amps (Resistive Load)
- GPA = General Purpose Amps (Inductive Load, 75 % to 80 % power factor)
- VL = Lamp Load
- XX (Y) = XX max. resistive value (Amps) and (Y) max. inductive value (Amps)

**FIGURE 1. PRODUCT NOMENCLATURE**

Switch Type	Temperature Grade	Electrical Rating	Terminal Type	Housing Type	Circuit Code	Operating Force (at pin plunger max)	Lever Position	Lever Type	Mounting Holes
<b>V19</b> V19 Series MICRO Switch	<b>S</b> -25°C to 85°C [-13°F to 185°F] <b>T</b> -25°C to 125°C [-13°F to 257°F]	<b>05</b> 5 GPA 125/250 Vac; 6 GPA 125/250 Vac 1/10 HP 125/250 Vac 0.4 RA 125 Vdc; 0.3 RA 250 Vdc 10,000 cycles <b>16</b> 16 GPA 125/250 Vac 1/2 HP 125/250 Vac 0.6 RA 125 Vdc; 0.3 RA 250 Vdc 10,000 cycles	<b>C</b> Quick connect 6,30 mm x 0,80 mm [0.250 in x 0.032 in] <b>E</b> Quick connect 4,70 mm x 0,50 mm [0.187 in x 0.020 in] <b>H</b> RAST 5 6,30 mm x 0,80 mm [0.250 in x 0.032 in] <b>N</b> RAST 7 6,30 mm x 0,80 mm [0.250 in x 0.032 in] <b>P</b> Straight PCB terminal <b>V</b> RAST 2.5 terminal	<b>Basic</b> <b>2</b> Fully flat <b>3</b> RAST 2.5	<b>Z</b> SPDT <b>P</b> SPST-NO <b>C</b> SPST-NC	<b>015</b> 15 gf; 0,15 N <b>025</b> 25 gf; 0,25 N <b>050</b> 50 gf; 0,5 N <b>100</b> 100 gf; 0,98 N <b>200</b> 200 gf; 1,96 N <b>300</b> 300 gf; 2,94 N <b>400</b> 400 gf; 3,92 N	<b>Pin plunger, no lever</b> <b>A</b> Far from pin plunger <b>B</b> Near pin plunger	<b>Plunger without lever</b> <b>01</b> Short straight lever <b>02</b> Standard straight lever <b>03</b> Long straight lever <b>04</b> Simulated roller lever <b>05</b> Roller lever <b>06</b> Long roller lever	<b>Metric Ø 3,1 mm</b> <b>K</b> USA Ø 2,9 mm

\* Temperature rating "S" is allowed only with electrical rating "05"  
 \* Temperature rating "T" is allowed only with electrical rating "16"  
 \* Terminal style "V" and housing type "3" are offered together, only allowed with electrical rating "05"  
 \* Operating forces 015, 025 and 050 are only allowed with electrical rating "05"  
 \* Operating forces 300 and 400 are only allowed with electrical rating "16"






**FIGURE 2. LOAD LIFE CURVE**

Graph coming soon.

- Current rating of a switch at a given voltage represents the maximum electrical load the switch is designed to control
- Based on connection of the circuit to either the normally open or normally closed throw of the switch
- Assumes the plunger of the switch is driven to full over travel and full release actuation

# MICRO SWITCH, V19 SERIES






**TABLE 3. CONFIGURATIONS AND CHARACTERISTICS**

LEVER POSITION	ACTUATION TYPE	ACTUATION PICTURE	APPLICABLE ELECTRICAL RATING	OPERATING FORCE CODE	MAX OPERATING FORCE (g)	MIN RELEASE FORCE (g)	OP (mm)	PT MAX. (mm)	DT MAX. (mm)	OT MIN. (mm)
A	Pin plunger		5 A	015	15	4	14,7 ±0,4	1,2	0,4	1,0
			5 A	025	25	5				
			5 A	050	50	8				
			5 A and 16 A	100	100	15				
			5 A and 16 A	200	200	50				
			16 A	300	300	75				
			16 A	400	400	79				
	Short straight (01)		5 A	015	15	4	15,2 ±0,5	1,6	1,2	0,8
			5 A	025	25	5				
			5 A	050	50	8				
			5 A and 16 A	100	100	15				
			5 A and 16 A	200	200	50				
			16 A	300	300	75				
			16 A	400	400	50				
	Standard straight (02)		5 A	015	10	2	15,2 ±1,2	4,0	2,0	1,6
			5 A	025	15	3				
			5 A	050	30	4				
			5 A and 16 A	100	50	10				
			5 A and 16 A	200	125	14.3				
			16 A	300	150	40				
			16 A	400	250	25.5				
	Long straight (03)		5 A	015	5	2	15,2 ±2,6	9,0	3,8	2,0
			5 A	025	10	2				
			5 A	050	15	3				
			5 A and 16 A	100	25	4				
			5 A and 16 A	200	70	6				
			16 A	300	100	15				
			16 A	400	130	12.2				
Simulated roller (04)		5 A	015	10	2	18,7 ±1,2	4,0	3,5	1,6	
		5 A	025	15	3					
		5 A	050	30	4					
		5 A and 16 A	100	50	10					
		5 A and 16 A	200	125	14.3					
		16 A	300	150	40					
		16 A	400	250	25.5					

Abbreviation	Term	Definition
OP	Operating Position	position that the switch contacts change state
PT	Pretravel	distance the actuator moves to trigger the switch
DT	Differential Travel	distance between the OP and the RP
OT	Overtravel	max distance the actuator can move past the OP
RP	Release Point	point that contacts return to free state from OP

# MICRO SWITCH, V19 SERIES





**TABLE 3. CONFIGURATIONS AND CHARACTERISTICS**

LEVER POSITION	ACTUATION TYPE	ACTUATION PICTURE	APPLICABLE ELECTRICAL RATING	OPERATING FORCE CODE	MAX OPERATING FORCE (g)	MIN RELEASE FORCE (g)	OP (mm)	PT MAX. (mm)	DT MAX. (mm)	OT MIN. (mm)
A	Roller lever (05)		5 A	015	30	4	20,7 ±0,6	1,6	0,9	0,8
			5 A	025	35	8				
			5 A	050	70	8				
			5 A and 16 A	100	140	15				
			5 A and 16 A	200	240	50				
			16 A	300	340	50				
			16 A	400	480	50				
	Long roller (06)		5 A	015	10	2	20,7 ±1,2	4,0	2,7	1,6
			5 A	025	15	2				
			5 A	050	30	4				
			5 A and 16 A	100	50	10				
			5 A and 16 A	200	125	14.3				
			16 A	300	150	40				
			16 A	400	250	25.5				
B	Pin plunger		5 A	015	15	2	14,7 ±0,4	1,2	0,4	1,0
			5 A	025	25	5				
			5 A	050	60	8				
			5 A and 16 A	100	100	15				
			5 A and 16 A	200	200	50				
			16 A	300	300	75				
			16 A	400	400	150				
	Short straight (01)		5 A	015	10	2	15,7 ± 0,5	2,0	1,2	1,1
			5 A	025	15	3				
			5 A	050	35	5				
			5 A and 16 A	100	65	8				
			5 A and 16 A	200	130	16				
			16 A	300	150	45				
			16 A	400	300	75				
	Standard straight (02)		5 A	015	5	2	15,9 ± 1,2	4,0	2,0	2,5
			5 A	025	10	2				
			5 A	050	20	3				
			5 A and 16 A	100	35	4				
5 A and 16 A			200	70	8					
16 A			300	75	25					
16 A			400	130	40					

Abbreviation	Term	Definition
OP	Operating Position	position that the switch contacts change state
PT	Pretravel	distance the actuator moves to trigger the switch
DT	Differential Travel	distance between the OP and the RP
OT	Overtravel	max distance the actuator can move past the OP
RP	Release Point	point that contacts return to free state from OP

# MICRO SWITCH, V19 SERIES

**TABLE 3. CONFIGURATIONS AND CHARACTERISTICS**

LEVER POSITION	ACTUATION TYPE	ACTUATION PICTURE	APPLICABLE ELECTRICAL RATING	OPERATING FORCE CODE	MAX OPERATING FORCE (g)	MIN RELEASE FORCE (g)	OP (mm)	PT MAX. (mm)	DT MAX. (mm)	OT MIN. (mm)
B	Long straight (03)		5 A	015	2	2	17,2 ± 2,6	9,0	3,8	4,0
			5 A	025	5	2				
			5 A	050	10	2				
			5 A and 16 A	100	20	2				
			5 A and 16 A	200	35	4				
			16 A	300	40	10				
			16 A	400	80	25				
	Simulated roller (04)		5 A	015	5	2	19,4 ± 1,2	4,0	3,5	2,0
			5 A	025	10	2				
			5 A	050	20	3				
			5 A and 16 A	100	40	3				
			5 A and 16 A	200	75	10				
			16 A	300	80	20				
			16 A	400	150	50				
	Roller lever (05)		5 A	015	10	2	21,0 ± 1,0	2,0	0,9	1,0
			5 A	025	15	3				
			5 A	050	35	3				
			5 A and 16 A	100	80	8				
			5 A and 16 A	200	160	15				
			16 A	300	200	40				
			16 A	400	350	100				
	Long roller lever (06)		5 A	015	5	2	21,4 ± 1,2	4,0	2,7	2,0
			5 A	025	2	10				
			5 A	050	20	5				
5 A and 16 A			100	40	3					
5 A and 16 A			200	75	10					
16 A			300	100	30					
16 A			400	150	50					

Abbreviation	Term	Definition
OP	Operating Position	position that the switch contacts change state
PT	Pretravel	distance the actuator moves to trigger the switch
DT	Differential Travel	distance between the OP and the RP
OT	Overtravel	max distance the actuator can move past the OP
RP	Release Point	point that contacts return to free state from OP

# MICRO SWITCH, V19 SERIES

## MOUNTING DIMENSIONS

FIGURE 3. V19 SERIES STANDARD SWITCH DIMENSIONS




FIGURE 4. V19 SERIES HOUSING DIMENSIONS






FIGURE 5. V19 SERIES RAST 2.5 SWITCH DIMENSIONS




# MICRO SWITCH, V19 SERIES

## CONNECTION DIMENSIONS


**FIGURE 6. V19 SERIES C-STYLE QUICK CONNECT •  
6,35 MM WIDE X 0,8 MM THICK [0.25 IN WIDE X 0.031 IN THICK]**




**FIGURE 7. V19 SERIES H-STYLE RAST-5 250#  
CONNECTOR**




**FIGURE 8. V19 SERIES E-STYLE QUICK CONNECT •  
4,80 MM WIDE X 0,5 MM THICK [0.189 IN WIDE X 0.020 IN THICK]**



**FIGURE 9. V19 SERIES N-STYLE RAST-7 250#  
CONNECTOR**




**FIGURE 10. V19 SERIES P-STYLE STRAIGHT PCB TERMINAL**




# MICRO SWITCH, V19 SERIES

## STANDARD LEVER OPTIONS • DIMENSIONS


**FIGURE 11. V19 SERIES A01/STRAIGHT SHORT LEVER**




**FIGURE 12. V19 SERIES A02/STANDARD STRAIGHT LEVER**




**FIGURE 13. V19 SERIES A03/LONG STRAIGHT LEVER**




**FIGURE 14. V19 SERIES A04/SIMULATED ROLLER LEVER**



**FIGURE 15. V19 SERIES A05/SHORT ROLLER LEVER**




**FIGURE 16. V19 SERIES A06/ROLLER LEVER**




NOTE: These dimensions apply for the "A" lever position. For the "B" lever position, please add 5,8 mm [0.224 in].




**Position A**



**Position B**



## HONEYWELL UNSEALED V BASIC PORTFOLIO

	V7	V15	V19
			
<b>Target Market</b>	Applications requiring precision, long term reliability, and design flexibility in electrical ratings	Cost sensitive applications requiring configurability in actuation, termination, and operating characteristics	Applications in major and small appliances or designs that require simple configurations
<b>Differentiator</b>	Wide range of max operating force and precise differential travel specs key for a more accurate switch actuation	Industry standard switch footprint and global certifications ideal for “low-cost-of-failure” applications	Provides balance between cost and performance in high-volume switch applications
<b>Options</b>	<b>MIL-PRF-8805 listings available</b> V3 family designed for rugged applications where reliability and repeatability is key	<b>Multiple Contact Material Options</b> Contact variants to enable design and regulation compliance	<b>RAST Termination</b> Multiple RAST standard terminal options for optimizing automated manufacturing processes

### RELATED DOCUMENTATION

- V Basics Range Guide
- Applying Precision Switches
- V7 Datasheet
- V15 Datasheet

### FOR MORE INFORMATION

Honeywell Advanced Sensing Technologies services its customers through a worldwide network of sales offices and distributors. For application assistance, current specifications, pricing, or the nearest Authorized Distributor, visit [sps.honeywell.com/ast](http://sps.honeywell.com/ast) or call:

USA/Canada	+302 613 4491
Latin America	+1 305 805 8188
Europe	+44 1344 238258
Japan	+81 (0) 3-6730-7152
Singapore	+65 6355 2828
Greater China	+86 4006396841

### Honeywell Advanced Sensing Technologies

830 East Arapaho Road  
Richardson, TX 75081  
[sps.honeywell.com/ast](http://sps.honeywell.com/ast)

### WARRANTY/REMEDY

Honeywell warrants goods of its manufacture as being free of defective materials and faulty workmanship during the applicable warranty period. Honeywell’s standard product warranty applies unless agreed to otherwise by Honeywell in writing; please refer to your order acknowledgment or consult your local sales office for specific warranty details. If warranted goods are returned to Honeywell during the period of coverage, Honeywell will repair or replace, at its option, without charge those items that Honeywell, in its sole discretion, finds defective. **The foregoing is buyer’s sole remedy and is in lieu of all other warranties, expressed or implied, including those of merchantability and fitness for a particular purpose. In no event shall Honeywell be liable for consequential, special, or indirect damages.**

While Honeywell may provide application assistance personally, through our literature and the Honeywell web site, it is buyer’s sole responsibility to determine the suitability of the product in the application.

Specifications may change without notice. The information we supply is believed to be accurate and reliable as of this writing. However, Honeywell assumes no responsibility for its use.

### **⚠ WARNING** **IMPROPER INSTALLATION**

- Consult with local safety agencies and their requirements when designing a machine-control link, interface and all control elements that affect safety.
- Strictly adhere to all installation instructions.

**Failure to comply with these instructions could result in death or serious injury.**

### **⚠ WARNING** **MISUSE OF DOCUMENTATION**

- The information presented in this product sheet is for reference only. Do not use this document as a product installation guide.
- Complete installation, operation, and maintenance information is provided in the instructions supplied with each product.

**Failure to comply with these instructions could result in death or serious injury.**