NTK3043N

MOSFET – Power, N-Channel with ESD Protection, SOT-723

20 V, 285 mA

ON Semiconductor®

www.onsemi.com

$V_{(BR)DSS}$	$R_{DS(on)}$ TYP	I_D Max
20 V	1.5 Ω @ 4.5 V	285 mA
	2.4 Ω @ 2.5 V	
	5.1 Ω @ 1.8 V	
	6.8 Ω @ 1.65 V	

Features

- Enables High Density PCB Manufacturing
- 44% Smaller Footprint than SC−89 and 38% Thinner than SC−89
- Low Voltage Drive Makes this Device Ideal for Portable Equipment
- Low Threshold Levels, $V_{GS(TH)}$ < 1.3 V
- Low Profile (< 0.5 mm) Allows It to Fit Easily into Extremely Thin Environments such as Portable Electronics
- Operated at Standard Logic Level Gate Drive, Facilitating Future Migration to Lower Levels Using the Same Basic Topology
- These are Pb−Free and Halogen−Free Devices

Applications

- Interfacing, Switching
- High Speed Switching
- Cellular Phones, PDAs

Top View



1 – Gate
2 – Source
3 – Drain

MAXIMUM RATINGS (T_J = 25°C unless otherwise stated)

Parameter			Symbol	Value	Unit
Drain−to−Source Voltage			V_{DSS}	20	V
Gate−to−Source Voltage			V_{GS}	±10	V
Continuous Drain Current (Note 1)	Steady State	T_A = 25°C	I_D	255	mA
		T_A = 85°C		185	
	t ≤ 5 s	T_A = 25°C		285	
Power Dissipation (Note 1)	Steady State	T_A = 25°C	P_D	440	mW
	t ≤ 5 s			545	
Continuous Drain Current (Note 2)	Steady State	T_A = 25°C	I_D	210	mA
		T_A = 85°C		155	
Power Dissipation (Note 2)		T_A = 25°C	P_D	310	mW
Pulsed Drain Current	t_p = 10 μs		I_{DM}	400	mA
Operating Junction and Storage Temperature			T_J, T_{STG}	−55 to 150	°C
Source Current (Body Diode) (Note 2)			I_S	286	mA
Lead Temperature for Soldering Purposes (1/8" from case for 10 seconds)			T_L	260	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Surface−mounted on FR4 board using 1 in sq pad size (Cu area = 1.127 in sq [1 oz] including traces)
2. Surface−mounted on FR4 board using the minimum recommended pad size.



SOT−723
CASE 631AA
STYLE 5

MARKING DIAGRAM



KA = Device Code
M = Date Code

ORDERING INFORMATION

Device	Package	Shipping†
NTK3043NT1G	SOT−723*	4000 / Tape & Reel
NTK3043NT5G	SOT−723*	8000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

*These packages are inherently Pb−Free.

© Semiconductor Components Industries, LLC, 2013

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Max	Unit
Junction−to−Ambient − Steady State (Note 3)	$R_{\theta JA}$	280	°C/W
Junction−to−Ambient − t = 5 s (Note 3)	$R_{\theta JA}$	228	
Junction−to−Ambient − Steady State Minimum Pad (Note 4)	$R_{\theta JA}$	400	

3. Surface−mounted on FR4 board using 1 in sq pad size (Cu area = 1.127 in sq [1 oz] including traces)
4. Surface−mounted on FR4 board using the minimum recommended pad size.

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise specified)

Parameter	Test Condition		Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS							
Drain−to−Source Breakdown Voltage	V_{GS} = 0 V, I_D = 100 μA		$V_{(BR)DSS}$	20			V
Drain−to−Source Breakdown Voltage Temperature Coefficient	I_D = 100 μA, Reference to 25°C		$V_{(BR)DSS}/T_J$		27		mV/°C
Zero Gate Voltage Drain Current	V_{GS} = 0 V, V_{DS} = 16 V	T_J = 25°C	I_{DSS}			1	μA
		T_J = 125°C				10	
Gate−to−Source Leakage Current	V_{DS} = 0 V, V_{GS} = ±5 V		I_{GSS}			1	μA
ON CHARACTERISTICS (Note 3)							
Gate Threshold Voltage	V_{GS} = V_{DS}, I_D = 250 μA		$V_{GS(TH)}$	0.4		1.3	V
Gate Threshold Temperature Coefficient			$V_{GS(TH)}/T_J$		−2.4		mV/°C
Drain−to−Source On Resistance	V_{GS} = 4.5V, I_D = 10 mA		$R_{DS(ON)}$		1.5	3.4	Ω
	V_{GS} = 4.5V, I_D = 255 mA				1.6	3.8	
	V_{GS} = 2.5 V, I_D = 1 mA				2.4	4.5	
	V_{GS} = 1.8 V, I_D = 1 mA				5.1	10	
	V_{GS} = 1.65 V, I_D = 1 mA				6.8	15	
Forward Transconductance	V_{DS} = 5 V, I_D = 100 mA		g_{FS}		0.275		S
Gate Resistance	T_A = 25°C		R_G		2.2		kΩ
CHARGES, CAPACITANCES AND GATE RESISTANCE							
Input Capacitance	V_{GS} = 0 V, f = 1 MHz, V_{DS} = 10 V		C_{ISS}		11		pF
Output Capacitance			C_{OSS}		8.3		
Reverse Transfer Capacitance			C_{RSS}		2.7		
SWITCHING CHARACTERISTICS, VGS= 4.5 V (Note 4)							
Turn−On Delay Time	V_{GS} = 4.5 V, V_{DD} = 5 V, I_D = 10 mA, R_G = 6 Ω		$t_{d(ON)}$		13		ns
Rise Time			t_r		15		
Turn−Off Delay Time			$t_{d(OFF)}$		94		
Fall Time			t_f		55		
DRAIN−SOURCE DIODE CHARACTERISTICS							
Forward Diode Voltage	V_{GS} = 0 V, I_S= 286 mA	T_J = 25°C	V_{SD}		0.83	1.2	V
		T_J = 125°C			0.69		
Reverse Recovery Time	V_{GS} = 0 V, V_{DD} = 20 V, dISD/dt = 100 A/μs, I_S = 286 mA		t_{RR}		9.1		ns
Charge Time			t_a		7.1		
Discharge Time			t_b		2.0		
Reverse Recovery Charge			Q_{RR}		3.7		nC

5. Pulse Test: pulse width ≤ 300 μs, duty cycle ≤ 2%
6. Switching characteristics are independent of operating junction temperatures

TYPICAL PERFORMANCE CURVES



Figure 1. On−Region Characteristics



Figure 2. Transfer Characteristics



Figure 3. On−Resistance vs. Gate−to−Source Voltage



Figure 4. On−Resistance vs. Drain Current and Gate Voltage



Figure 5. On−Resistance Variation with Temperature



Figure 6. Drain−to−Source Leakage Current vs. Voltage

TYPICAL PERFORMANCE CURVES



Figure 7. Capacitance Variation



Figure 8. Resistive Switching Time Variation vs. Gate Resistance



Figure 9. Diode Forward Voltage vs. Current



SOT−723 1.20x0.80x0.50, 0.40P
CASE 631AA
ISSUE E

DATE 24 JAN 2024

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2018.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS.

DIM	MILLIMETERS		
	MIN.	NOM.	MAX.
A	0.45	0.50	0.55
b	0.15	0.21	0.27
b1	0.25	0.31	0.37
c	0.07	0.12	0.17
D	1.15	1.20	1.25
E	0.75	0.80	0.85
e	0.40 BSC		
H	1.15	1.20	1.25
L	0.29 REF		
L2	0.15	0.20	0.25



TOP VIEW



SIDE VIEW



BOTTOM VIEW



RECOMMENDED MOUNTING FOOTPRINT

*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

GENERIC MARKING DIAGRAM*



XX = Specific Device Code
M = Date Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

STYLE 1:
PIN 1. BASE
2. EMITTER
3. COLLECTOR

STYLE 2:
PIN 1. ANODE
2. N/C
3. CATHODE

STYLE 3:
PIN 1. ANODE
2. ANODE
3. CATHODE

STYLE 4:
PIN 1. CATHODE
2. CATHODE
3. ANODE

STYLE 5:
PIN 1. GATE
2. SOURCE
3. DRAIN

DOCUMENT NUMBER:	98AON12989D	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	SOT−723 1.20x0.80x0.50, 0.40P	PAGE 1 OF 1

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales