

Printed-circuit board connector - DFK-MSTB 2,5/ 2-G-5,08 WW(1X1) - 0707882

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Feed-through header, number of positions: 2, pitch: 5.08 mm, color: green


The figure shows the version with solder/spade connections

Your advantages

- Maximum flexibility when it comes to device design – one header for connectors with different connection technologies
- Cable connection on the inside of the device enables flexible positioning of the panel feed-through



Key Commercial Data

Packing unit	50 pc
GTIN	 4 017918 004279
GTIN	4017918004279

Technical data

Dimensions

Length [l]	17.5 mm
Width	30.48 mm
Pitch	5.08 mm
Dimension a	5.08 mm
Width [w]	30.48 mm
Height [h]	29.5 mm
Height	20.2 mm
Length of the solder pin	9.3 mm
Length	17.5 mm

General

Range of articles	DFK-MSTB 2,5/..-G
-------------------	-------------------

Printed-circuit board connector - DFK-MSTB 2,5/ 2-G-5,08 WW(1X1) - 0707882

Technical data

General

Rated voltage (III/3)	320 V
Connection in acc. with standard	EN-VDE
Nominal current I _N	12 A
Color	green
Number of positions	2

Standards and Regulations

Connection in acc. with standard	EN-VDE
	CUL

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals


Approvals


Approvals

EAC / cULus Recognized

Ex Approvals

Approval details

EAC		B.01742
-----	---	---------

cULus Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E60425-19931011
	D	B	
Nominal voltage U _N	300 V	300 V	
Nominal current I _N	10 A	15 A	

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>