

## Shrink sleeve - MM-WMS-2 4,8 (EX9)R C1 WH/BK - 0803928


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Shrink sleeve, continuous, cassette, white with black imprint, mounting type: slide-on, cable diameter: 2.4 - 4.8 mm, can be marked with THERMOFOX



### Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 212081
GTIN	4055626212081
Weight per Piece (excluding packing)	40.000 g
Custom tariff number	39173200
Country of origin	China

### Technical data

#### Dimensions

Length (b)	1.8 m
Width (a)	9 mm
Cable diameter	2.4 mm ... 4.8 mm

#### Ambient conditions

Ambient temperature (operation)	-55 °C ... 135 °C
---------------------------------	-------------------

#### General

Color	white
Base element material	polyolefine
Components	free from silicone, halogen, and cadmium
Material	Polyolefine

## Shrink sleeve - MM-WMS-2 4,8 (EX9)R C1 WH/BK - 0803928

### Technical data

#### General

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Marking mounting type	slide on

#### Standards and Regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------