

Reducing adapter - A-INR-PG29/21-N-NS-S - 1415218

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Reducing adapter, Nickel-plated brass, Connecting thread: Pg29

The figure shows version A-INR-PG21/16-N-NS-S

Product Description

Reduces Pg29 to Pg21



Key Commercial Data

| | |
|------------------------|----------|
| Packing unit | 1 STK |
| Minimum order quantity | 10 STK |
| Custom tariff number | 74153900 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|----------------------------------|--------|
| Length | 9.5 mm |
| Length without connecting thread | 3 mm |
| Connecting thread diameter | 23 mm |
| Hexagon angular dimension | 27 mm |
| Length of the connecting thread | 6.5 mm |

Ambient conditions

| | |
|----------------------|---|
| Degree of protection | IP68 (Depends on the screw connection used) |
|----------------------|---|

General

| | |
|-----------------|---------------------|
| Material | Nickel-plated brass |
| O-ring material | NBR |

Reducing adapter - A-INR-PG29/21-N-NS-S - 1415218


Technical data

General

| | |
|-----------------|------|
| Outer thread | Pg29 |
| Internal thread | Pg21 |

Drawings

Dimensional drawing



Dimensional drawing

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 5.1 | 27149109 |
| eCl@ss 6.0 | 27149109 |
| eCl@ss 8.0 | 27149109 |
| eCl@ss 9.0 | 27144432 |

ETIM

| | |
|----------|----------|
| ETIM 5.0 | EC000441 |
| ETIM 6.0 | EC000441 |

UNSPSC

| | |
|-------------|----------|
| UNSPSC 13.2 | 39121311 |
|-------------|----------|