

## Base strip - IPC 5/ 4-GFU-7,62 - 1708734

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


Header, Nominal current: 41 A, Rated voltage (III/2): 630 V, Number of positions: 4, Pitch: 7.62 mm, Color: green, Contact surface: Tin, Mounting: Wave soldering



The figure shows a 5-pos. version of the product

### Product Features

- PCB-SHIELD shroud for a professional EMC shield connection
- Maximum contact reliability due to integrated double steel spring
- Inverted IPC 5 headers for implementing a touch-proof PCB output or a PCB/PCB connection (in combination with PC 5 base strips)



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 50 pc    |
| Weight per Piece (excluding packing) | 12.6 g   |
| Custom tariff number                 | 85366990 |
| Country of origin                    | Germany  |

### Technical data

#### Dimensions

|                          |          |
|--------------------------|----------|
| Length                   | 30.1 mm  |
| Pitch                    | 7.62 mm  |
| Dimension a              | 22.86 mm |
| Constructional height    | 12.8 mm  |
| Length of the solder pin | 5 mm     |
| Pin dimensions           | 1,2x0,8  |
| Pin spacing              | 7.62 mm  |
| Hole diameter            | 1.3 mm   |

## Base strip - IPC 5/ 4-GFU-7,62 - 1708734

### Technical data

#### General

|  |              |
|--|--------------|
| Range of articles                      | IPC 5/...GFU |
| Insulating material group              | I            |
| Rated surge voltage (III/3)            | 6 kV         |
| Rated surge voltage (III/2)            | 6 kV         |
| Rated surge voltage (II/2)             | 6 kV         |
| Rated voltage (III/3)                  | 630 V        |
| Rated voltage (III/2)                  | 630 V        |
| Rated voltage (II/2)                   | 1000 V       |
| Connection in acc. with standard       | EN-VDE       |
| Nominal current I <sub>N</sub>         | 41 A         |
| Maximum load current                   | 41 A         |
| Insulating material                    | PA           |
| Flammability rating according to UL 94 | V0           |
| Color                                  | green        |
| Number of positions                    | 4            |

#### Standards and Regulations

|  |        |
|--|--------|
| Connection in acc. with standard       | EN-VDE |
|  | CUL    |
| Flammability rating according to UL 94 | V0     |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440402 |
| eCl@ss 9.0 | 27440402 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002637 |
| ETIM 5.0 | EC002637 |

# Base strip - IPC 5/ 4-GFU-7,62 - 1708734

## Classifications

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11     | 39121409 |
| UNSPSC 12.01  | 39121409 |
| UNSPSC 13.2   | 39121409 |

## Approvals

### Approvals

---

#### Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

---


#### Ex Approvals


---

#### Approvals submitted

---

## Approval details

|   |       |       |       |
|---|-------|-------|-------|
| UL Recognized  |       |       |       |
|   | B     | C     | D     |
| Nominal current I <sub>N</sub>  | 41 A  | 41 A  | 5 A   |
| Nominal voltage U <sub>N</sub>  | 300 V | 300 V | 600 V |

|  |       |       |       |
|--|-------|-------|-------|
| cUL Recognized  |       |       |       |
|  | B     | C     | D     |
| Nominal current I <sub>N</sub>   | 41 A  | 41 A  | 5 A   |
| Nominal voltage U <sub>N</sub>   | 300 V | 300 V | 600 V |

|     |
|-----|
| EAC |
|-----|


# Base strip - IPC 5/ 4-GFU-7,62 - 1708734

## Approvals



## Drawings

Drilling diagram



Dimensional drawing

