

## Printed-circuit board connector - GMVSTBR 2,5/ 3-ST-7,62 BK - 1903122

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


PCB connector, nominal current: 12 A, rated voltage (III/2): 630 V, nominal cross section: 2.5 mm<sup>2</sup>, number of positions: 3, pitch: 7.62 mm, connection method: Screw connection with tension sleeve, color: black, contact surface: Tin



The figure shows a 10-position version of the product

### Your advantages

- ✓ Well-known connection principle allows worldwide use
- ✓ Low temperature rise, thanks to maximum contact force
- ✓ Larger pitch for increased voltage requirements
- ✓ Allows connection of two conductors



### Key Commercial Data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 50 pc                                                                                                   |
| Minimum order quantity               | 50 pc                                                                                                   |
| GTIN                                 | <br>4 017918 437954 |
| GTIN                                 | 4017918437954                                                                                           |
| Weight per Piece (excluding packing) | 6.980 g                                                                                                 |
| Custom tariff number                 | 85366990                                                                                                |
| Country of origin                    | Germany                                                                                                 |
| Note                                 | Made to Order (non-returnable)                                                                          |

### Technical data

#### Item properties

|                           |                                 |
|---------------------------|---------------------------------|
| Brief article description | Printed-circuit board connector |
| Plug-in system            | CLASSIC COMBICON                |
| Type of contact           | Female connector                |
| Range of articles         | GMVSTBR 2,5/...-ST              |
| Pitch                     | 7.62 mm                         |
| Number of positions       | 3                               |

# Printed-circuit board connector - GMVSTBR 2,5/ 3-ST-7,62 BK - 1903122

## Technical data

### Item properties

|                       |                                      |
|-----------------------|--------------------------------------|
| Connection method     | Screw connection with tension sleeve |
| Drive form screw head | Slotted (L)                          |
| Locking               | without                              |
| Number of levels      | 1                                    |
| Number of connections | 3                                    |
| Number of potentials  | 3                                    |

### Electrical parameters

|                             |        |
|-----------------------------|--------|
| Nominal current             | 12 A   |
| Nom. voltage                | 630 V  |
| Rated voltage               | 500 V  |
| Rated voltage (III/2)       | 630 V  |
| Rated voltage (II/2)        | 1000 V |
| Rated surge voltage (III/3) | 6 kV   |
| Rated surge voltage (III/2) | 6 kV   |
| Rated surge voltage (II/2)  | 6 kV   |

### Connection capacity

|                                                                                           |                                              |
|-------------------------------------------------------------------------------------------|----------------------------------------------|
| Connection method                                                                         | Screw connection with tension sleeve         |
| pluggable                                                                                 | Yes                                          |
| Conductor cross section solid                                                             | 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>  |
| Conductor cross section flexible                                                          | 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>  |
| Conductor cross section AWG / kcmil                                                       | 24 ... 12                                    |
| Conductor cross section flexible, with ferrule without plastic sleeve                     | 0.25 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Conductor cross section, flexible, with ferrule, with plastic sleeve                      | 0.25 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| 2 conductors with same cross section, solid                                               | 0.2 mm <sup>2</sup> ... 1 mm <sup>2</sup>    |
| 2 conductors with same cross section, flexible                                            | 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, flexible, with ferrule without plastic sleeve       | 0.25 mm <sup>2</sup> ... 1 mm <sup>2</sup>   |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.5 mm <sup>2</sup> ... 1 mm <sup>2</sup>    |
| Cylindrical gauge a x b / diameter                                                        | 2.8 mm x 2.4 mm / 2.5 mm                     |
| Stripping length                                                                          | 7 mm                                         |
| Torque                                                                                    | 0.5 Nm ... 0.6 Nm                            |

### Flange specifications

|                 |         |
|-----------------|---------|
| Type of locking | without |
| Mounting flange | without |

### Material data - contact

|                         |                                                                                   |
|-------------------------|-----------------------------------------------------------------------------------|
| Note                    | WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/ JEDEC JESD 201 |
| Contact material        | Cu alloy                                                                          |
| Surface characteristics | hot-dip tin-plated                                                                |

# Printed-circuit board connector - GMVSTBR 2,5/ 3-ST-7,62 BK - 1903122

## Technical data

### Material data - contact

|                                          |                   |
|------------------------------------------|-------------------|
| Metal surface terminal point (top layer) | Tin (4 - 8 µm Sn) |
| Metal surface contact area (top layer)   | Tin (4 - 8 µm Sn) |

### Material data - housing

|                                                                   |              |
|-------------------------------------------------------------------|--------------|
| Housing color                                                     | black (9005) |
| Insulating material                                               | PA           |
| Insulating material group                                         | I            |
| CTI according to IEC 60112                                        | 600          |
| Flammability rating according to UL 94                            | V0           |
| Glow wire flammability index GWFI according to EN 60695-2-12      | 850          |
| Glow wire ignition temperature GWIT according to EN 60695-2-13    | 775          |
| Temperature for the ball pressure test according to EN 60695-10-2 | 125 °C       |

### Dimensions for the product

|                             |          |
|-----------------------------|----------|
| Length [ l ]                | 12.6 mm  |
| Width [ w ]                 | 20.82 mm |
| Height [ h ]                | 26 mm    |
| Pitch                       | 7.62 mm  |
| Height (without solder pin) | 26 mm    |

### Packaging information

|                            |                     |
|----------------------------|---------------------|
| Type of packaging          | packed in cardboard |
| Pieces per package         | 50                  |
| Denomination packing units | Pcs.                |

### Ambient conditions

|                                         |                                                     |
|-----------------------------------------|-----------------------------------------------------|
| Ambient temperature (storage/transport) | -40 °C ... 70 °C                                    |
| Ambient temperature (assembly)          | -5 °C ... 100 °C                                    |
| Ambient temperature (operation)         | -40 °C ... 100 °C (dependent on the derating curve) |

### Termination and connection method

|                                          |                     |
|------------------------------------------|---------------------|
| Test for conductor damage and slackening | IEC 60999-1:1999-11 |
|                                          | Test passed         |

### Pull-out test

|                                                          |                              |
|----------------------------------------------------------|------------------------------|
| Pull-out test                                            | IEC 60999-1:1999-11          |
|                                                          | Test passed                  |
| Conductor cross section / conductor type / tensile force | 0.14 mm² / solid / > 10 N    |
|                                                          | 0.14 mm² / flexible / > 10 N |
|                                                          | 2.5 mm² / solid / > 50 N     |
|                                                          | 2.5 mm² / flexible / > 50 N  |

### Mechanical tests according to standard

|                    |                                   |
|--------------------|-----------------------------------|
| Test specification | IEC 61984                         |
| Visual examination | Test passed IEC 60512-1-1:2002-02 |

# Printed-circuit board connector - GMVSTBR 2,5/ 3-ST-7,62 BK - 1903122

## Technical data

### Mechanical tests according to standard

|                                     |                                    |
|-------------------------------------|------------------------------------|
| Dimensional test                    | Test passed IEC 60512-1-2:2002-02  |
| Resistance of marking               | Test passed IEC 60068-2-70:1995-12 |
| Result                              | Test passed                        |
| Specification                       | IEC 60512-13-2:2006-02             |
| No. of cycles                       | 25                                 |
| Insertion strength per pos. approx. | 8 N                                |
| Withdraw strength per pos. approx.  | 6 N                                |
| Polarization and coding             | Test passed IEC 60512-13-5:2006-02 |
| Result                              | Test passed                        |
| Specification                       | IEC 60512-15-1:2008-05             |
| Test force per pos.                 | 31 N                               |

### Air clearances and creepage distances

|                                                 |                                                     |
|-------------------------------------------------|-----------------------------------------------------|
| Clearances and creepage distances               | IEC 60664-1:2007-04                                 |
| Specification                                   | IEC 60664-1:2007-04                                 |
| Minimum clearance - inhomogeneous field (III/3) | 5.5 mm                                              |
| Minimum clearance - inhomogeneous field (III/2) | 5.5 mm                                              |
| Minimum clearance - inhomogeneous field (II/2)  | 5.5 mm                                              |
| Minimum creepage distance value (III/3)         | 6.3 mm                                              |
| Minimum creepage distance value (III/2)         | 5.5 mm                                              |
| Minimum creepage distance value (II/2)          | 5.5 mm                                              |
| Note on connection cross section                | With connected conductor 4 mm <sup>2</sup> (solid). |

### Current carrying capacity / derating curves

|               |           |
|---------------|-----------|
| Specification | IEC 61984 |
|---------------|-----------|

### Mechanical tests (A)

|                                              |             |
|----------------------------------------------|-------------|
| Test specification                           | IEC 61984   |
| Insertion strength per pos. approx.          | 8 N         |
| Withdraw strength per pos. approx.           | 6 N         |
| Polarization when inserted requirement >20 N | Test passed |
| Contact holder in insert requirements >20 N  | Test passed |

### Durability tests (B)

|                                              |                       |
|----------------------------------------------|-----------------------|
| Specification                                | IEC 60512-9-1:2010-03 |
| Contact resistance R <sub>1</sub>            | 3.7 mΩ                |
| Insertion/withdrawal cycles                  | 25                    |
| Contact resistance R <sub>2</sub>            | 3.8 mΩ                |
| Impulse withstand voltage at sea level       | 7.3 kV                |
| Power-frequency withstand voltage            | 3.31 kV               |
| Insulation resistance, neighboring positions | > 2 TΩ                |

### Climatic tests (D)

## Printed-circuit board connector - GMVSTBR 2,5/ 3-ST-7,62 BK - 1903122

### Technical data

#### Climatic tests (D)

|                                        |                                                                           |
|----------------------------------------|---------------------------------------------------------------------------|
| Specification                          | ISO 6988:1985-02                                                          |
| Cold stress                            | -40 °C/2 h                                                                |
| Thermal stress                         | 100 °C/168 h                                                              |
| Corrosive stress                       | 0.2 dm <sup>3</sup> SO <sub>2</sub> on 300 dm <sup>3</sup> /40 °C/1 cycle |
| Impulse withstand voltage at sea level | 7.3 kV                                                                    |
| Power-frequency withstand voltage      | 3.31 kV                                                                   |

#### Environmental and durability tests (E)


|                                       |                                     |
|---------------------------------------|-------------------------------------|
| Specification                         | IEC 61984:2008-10                   |
| Result, degree of protection, IP code | Finger safety with IP20 test finger |

#### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| REACH SVHC | Lead 7439-92-1                                                                                      |
| China RoHS | Environmentally Friendly Use Period = 50 years                                                      |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

### Drawings


Diagram



Type: GMVSTBR 2,5 HV/...-ST-7,62 with GMSTBVA 2,5/...-G-7,62

## Printed-circuit board connector - GMVSTBR 2,5/ 3-ST-7,62 BK - 1903122

Diagram



Type: GMVSTB(R/W) 2,5/...-ST-7,62 with GMSTBV 2,5/...-G-7,62

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27260700 |
| eCl@ss 4.1 | 27260700 |
| eCl@ss 5.0 | 27260700 |
| eCl@ss 5.1 | 27260700 |
| eCl@ss 6.0 | 27260700 |
| eCl@ss 7.0 | 27440309 |
| eCl@ss 8.0 | 27440309 |
| eCl@ss 9.0 | 27440309 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002638 |
| ETIM 5.0 | EC002638 |
| ETIM 6.0 | EC002638 |
| ETIM 7.0 | EC002638 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11     | 39121409 |
| UNSPSC 12.01  | 39121409 |
| UNSPSC 13.2   | 39121409 |

# Printed-circuit board connector - GMVSTBR 2,5/ 3-ST-7,62 BK - 1903122

## Classifications

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 18.0 | 39121409 |
| UNSPSC 19.0 | 39121409 |
| UNSPSC 20.0 | 39121409 |
| UNSPSC 21.0 | 39121409 |

## Approvals

### Approvals

#### Approvals

CSA / IECCEB CB Scheme / EAC / cULus Recognized / VDE Zeichengenehmigung

#### Ex Approvals

### Approval details

|                    |                                                                                     |                                                                                                                                         |                 |
|--------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| CSA                |  | <a href="http://www.csagroup.org/services-industries/product-listing/">http://www.csagroup.org/services-industries/product-listing/</a> | LR13631-2585950 |
|                    | B                                                                                   | D                                                                                                                                       |                 |
| Nominal voltage UN | 300 V                                                                               | 300 V                                                                                                                                   |                 |
| Nominal current IN | 10 A                                                                                | 10 A                                                                                                                                    |                 |
| mm²/AWG/kcmil      | 28-12                                                                               | 28-12                                                                                                                                   |                 |

|                    |                                                                                     |                                                           |                |
|--------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|----------------|
| IECEE CB Scheme    |  | <a href="http://www.iecee.org/">http://www.iecee.org/</a> | DE1-60988-B1B2 |
| Nominal voltage UN | 400 V                                                                               |                                                           |                |
| Nominal current IN | 12 A                                                                                |                                                           |                |
| mm²/AWG/kcmil      | 0.2-2.5                                                                             |                                                           |                |

|     |                                                                                     |         |
|-----|-------------------------------------------------------------------------------------|---------|
| EAC |  | B.01687 |
|-----|-------------------------------------------------------------------------------------|---------|

## Printed-circuit board connector - GMVSTBR 2,5/ 3-ST-7,62 BK - 1903122

### Approvals

|                                                                                                                                                                                                                                                                          |       |       |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------|
| cULus Recognized  <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> E60425-19931013 |       |       |
|                                                                                                                                                                                                                                                                          | B     | D     |
| Nominal voltage UN                                                                                                                                                                                                                                                       | 300 V | 300 V |
| Nominal current IN                                                                                                                                                                                                                                                       | 15 A  | 10 A  |
| mm²/AWG/kcmil                                                                                                                                                                                                                                                            | 30-12 | 30-12 |

|                                                                                                                                                                                                                                                                                                                             |         |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| VDE Zeichengenehmigung  <a href="http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx">http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx</a> 40050646 |         |
|                                                                                                                                                                                                                                                                                                                             |         |
| Nominal voltage UN                                                                                                                                                                                                                                                                                                          | 400 V   |
| Nominal current IN                                                                                                                                                                                                                                                                                                          | 12 A    |
| mm²/AWG/kcmil                                                                                                                                                                                                                                                                                                               | 0.2-2.5 |