

Cable - FLK 20/2FLK14/EZ-DR/400/KONFEK



2305237

<https://www.phoenixcontact.com/gb/products/2305237>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Round cable set; connection 1: IDC/FLK socket strip (1x 20-position); connection 2: IDC/FLK socket strip (2x 14-position); cable length: 4 m

Your advantages

- Suitable for connecting 16-channel digital cards, e.g., SIMATIC[®] ET 200SP
- The 16 digital signals are split into 2x 8 signals on the field side
- IDC/FLK connector: 20-pos. to two 14-pos. (in accordance with IEC 60603-13)

Commercial Data

Item number	2305237
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	CK2131
Product Key	CK2131
GTIN	4046356038928
Weight per Piece (including packing)	348 g
Weight per Piece (excluding packing)	329 g
Customs tariff number	85444290
Country of origin	DE

Technical Data

Product properties

Product type	System cable
Insulation characteristics	
Overvoltage category	II
Pollution degree	2
Insulation	Functional insulation

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP00
Degree of protection Installation location	≥ IP54 (Installation location)
Ambient temperature (operation)	-40 °C ... 70 °C (fixed installation) -10 °C ... 70 °C (flexible installation)
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	≤ 2000 m

Electrical properties

Max. permissible operating voltage	25 V AC
	60 V DC
Nominal operating mode	100% operating factor
Max. current carrying capacity per path	1 A (50 °C)
	0.6 A (70 °C)
Rated insulation voltage	63 V
Rated surge voltage	0.6 kV

Supported controller EMERSON DeltaV

Suitable I/O card	VE4001S2T2B5
	VE4002S1T2B6

Supported controller SIEMENS ET 200SP

Suitable base unit	6ES7193-6BP00-0BA0
	6ES7193-6BP00-2BA0
	6ES7193-6BP00-0BA1
	6ES7193-6BP00-0DA0
	6ES7193-6BP00-2DA0
	6ES7193-6BP00-0DA1
Suitable I/O module	6ES7131-6BH01-0BA0 (Base Units A0/A1)
	6ES7131-6BH01-2BA0 (Base Units A0/A1)
	6ES7132-6BH01-0BA0 (Base Units A0/A1)
	6ES7132-6BH01-2BA0 (Base Units A0/A1)

Cable - FLK 20/2FLK14/EZ-DR/400/KONFEK



2305237

<https://www.phoenixcontact.com/gb/products/2305237>

Cable / line

Cable length	4 m
--------------	-----

20X0.14 [PVC]

UL AWM Style	2464/1061
Number of positions	20
Shielded	no
Cable type	20X0.14 [PVC]
Conductor type	Round cable set
Conductor structure signal line	7x 0.16 mm
AWG signal line	26
Conductor cross section	20x 0.14 mm ²
Wire diameter incl. insulation	1 mm ±0.03 mm
External cable diameter	7.6 mm ±0.4 mm
Outer sheath, material	Semi-rigid PVC
External sheath, color	gray
Conductor material	Tin-plated Cu litz wires
Cable resistance	≤ 145 Ω/km (20 °C)
Insulation resistance	≥ 20 MΩ*km (20 °C)
Smallest bending radius, fixed installation	64 mm
Smallest bending radius, movable installation	120 mm
Max. bending cycles	5000 (at a radius of ≥ 15x outside diameter)
Halogen-free	no
Flame resistance	IEC 60332-1-2 (raw cable)
	VDE 0842, Part 332-1-2 (raw cable)
	IEC 60332-3-22 (raw cable)
	UL VW-1
	CSA FT-1
Resistance to oil	can withstand occasional splashes (raw cable)
Type	Splitting cable for two modules
Cable, preassembly	Insulation displacement, IEC 60352-4/DIN EN 60352-4

color code

IDC/FLK20 (1)	IDC/FLK14-1 (1) = black
IDC/FLK20 (2)	IDC/FLK14-1 (2) = brown
IDC/FLK20 (3)	IDC/FLK14-1 (3) = red
IDC/FLK20 (4)	IDC/FLK14-1 (4) = orange
IDC/FLK20 (5)	IDC/FLK14-1 (5) = yellow
IDC/FLK20 (6)	IDC/FLK14-1 (6) = green
IDC/FLK20 (7)	IDC/FLK14-1 (7) = blue
IDC/FLK20 (8)	IDC/FLK14-1 (8) = violet
IDC/FLK20 (9)	IDC/FLK14-2 (1) = gray
IDC/FLK20 (10)	IDC/FLK14-2 (2) = white
IDC/FLK20 (11)	IDC/FLK14-2 (3) = white-black

2305237

<https://www.phoenixcontact.com/gb/products/2305237>

IDC/FLK20 (12)	IDC/FLK14-2 (4) = white-brown
IDC/FLK20 (13)	IDC/FLK14-2 (5) = white-red
IDC/FLK20 (14)	IDC/FLK14-2 (6) = white-orange
IDC/FLK20 (15)	IDC/FLK14-2 (7) = white-yellow
IDC/FLK20 (16)	IDC/FLK14-2 (8) = white-green
IDC/FLK20 (17)	IDC/FLK14-2 (9) = white-blue
IDC/FLK20 (18)	IDC/FLK14-2 (10) = white-violet
IDC/FLK20 (19)	IDC/FLK14-1 (9) = white-gray
IDC/FLK20 (20)	IDC/FLK14-1 (10) = brown-black

Connection data

Field level

Connection in acc. with standard	IEC 60603-13
Connection method	IDC/FLK socket strip
Number of connections	2
Number of positions	14
Insertion/withdrawal cycles	> 50
Pitch	2.54 mm

Controller level

Connection in acc. with standard	IEC 60603-13
Connection method	IDC/FLK socket strip
Number of connections	1
Number of positions	20
Insertion/withdrawal cycles	> 50
Pitch	2.54 mm


Standards and regulations

Air clearances and creepage distances

Standards/regulations	DIN EN 50178
-----------------------	--------------

Drawings

Diagram



Maximum permissible current per path in uncoiled state

Cable - FLK 20/2FLK14/EZ-DR/400/KONFEK



2305237

<https://www.phoenixcontact.com/gb/products/2305237>

Approvals



EAC

Approval ID: RU*-DE.HB*35.B00385



UL Listed

Approval ID: FILE E 238705

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	125 V	1 A	-	-



cUL Listed

Approval ID: FILE E 238705

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	125 V	1 A	-	-

cULus Listed

Cable - FLK 20/2FLK14/EZ-DR/400/KONFEK



2305237

<https://www.phoenixcontact.com/gb/products/2305237>

Classifications

ECLASS

ECLASS-9.0	27242220
ECLASS-10.0.1	27242220
ECLASS-11.0	27242220

ETIM

ETIM 8.0	EC000237
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

Cable - FLK 20/2FLK14/EZ-DR/400/KONFEK



2305237

<https://www.phoenixcontact.com/gb/products/2305237>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk