

# PT-IQ-5-HF+F-5DC-PT - Surge protection device



2801292

<https://www.phoenixcontact.com/nl/products/2801292>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Surge protection, consisting of protective plug and base element, with integrated multi-stage status indicator on the module for five signal wires. For HF applications and telecommunications interfaces without supply voltage (up to 90 Mbps). Can be used in safety-related circuits up to SIL 3.

## Your advantages

- Predictive monitoring with 3-stage LED display
- Integration of the status message into the system controller via group remote signaling
- Install quickly and error-free with DIN rail connectors
- Maximum ease of maintenance, thanks to the 2-piece design
- Maximum protection for MCR applications with high discharge capacity

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 2801292       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | CL2153        |
| Product key                          | CL2153        |
| GTIN                                 | 4046356766739 |
| Weight per piece (including packing) | 128,7 g       |
| Weight per piece (excluding packing) | 122,7 g       |
| Customs tariff number                | 85363010      |
| Country of origin                    | DE            |

# PT-IQ-5-HF+F-5DC-PT - Surge protection device



2801292  
<https://www.phoenixcontact.com/nl/products/2801292>

## Technical data

### Notes

|         |                                                                                                                                                     |
|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| General |                                                                                                                                                     |
| Note    | Remote signaling as well as the power supply of the DIN rail connector are established by snapping the module into place on the DIN rail connector. |

### Product properties

|                         |                                         |
|-------------------------|-----------------------------------------|
| Product family          | PLUGTRAB IQ                             |
| IEC test classification | C1                                      |
|                         | C2                                      |
|                         | C3                                      |
|                         | D1                                      |
| Type                    | DIN rail module, two-section, divisible |

|                            |     |
|----------------------------|-----|
| Insulation characteristics |     |
| Overvoltage category       | III |
| Pollution degree           | 2   |

### Electrical properties

|                       |        |
|-----------------------|--------|
| Nominal voltage $U_N$ | 5 V DC |
|-----------------------|--------|


### Connection data

|                                  |                     |
|----------------------------------|---------------------|
| Connection method                | Push-in connection  |
| Conductor cross-section flexible | 0.2 mm² ... 2.5 mm² |
| Conductor cross-section rigid    | 0.2 mm² ... 4 mm²   |
| Conductor cross-section AWG      | 24 ... 12           |

### Interfaces

|                    |         |
|--------------------|---------|
| Transmission speed | 90 Mbps |
|--------------------|---------|

### Dimensions

|                     |                                                                                      |
|---------------------|--------------------------------------------------------------------------------------|
| Dimensional drawing |  |
| Width               | 17.7 mm                                                                              |
| Height              | 109.3 mm                                                                             |
| Depth               | 77.5 mm (incl. DIN rail 7.5 mm)                                                      |
| Horizontal pitch    | 1 Div.                                                                               |

### Material specifications

# PT-IQ-5-HF+F-5DC-PT - Surge protection device



2801292

<https://www.phoenixcontact.com/nl/products/2801292>

|                                        |                  |
|----------------------------------------|------------------|
| Color                                  | black (RAL 9005) |
|                                        | black (RAL 9005) |
| Flammability rating according to UL 94 | V-0              |
| Housing material                       | PA 6.6           |

## Mechanical properties

### Mechanical data

|                 |    |
|-----------------|----|
| Open side panel | No |
|-----------------|----|

## Protective circuit

|                                                                 |                                                                                    |
|-----------------------------------------------------------------|------------------------------------------------------------------------------------|
| Direction of action                                             | Line-Line & Line-Signal Ground/Shield & optional Signal Ground/Shield-Earth Ground |
| Nominal voltage $U_N$                                           | 5 V DC                                                                             |
| Maximum continuous operating voltage $U_C$                      | 6 V DC                                                                             |
|                                                                 | 4 V AC                                                                             |
| Rated current                                                   | 600 mA (40 °C)                                                                     |
| Operating effective current $I_C$ at $U_C$                      | $\leq 800 \mu A$ (per path)                                                        |
| Protective conductor current $I_{PE}$                           | $\leq 10 \mu A$ (per path)                                                         |
| Nominal discharge current $I_n$ (8/20) $\mu s$ (line-line)      | 10 kA                                                                              |
| Nominal discharge current $I_n$ (8/20) $\mu s$ (line-ground)    | 10 kA                                                                              |
| Pulse discharge current $I_{imp}$ (10/350) $\mu s$ (line-earth) | 2.5 kA                                                                             |
| Total discharge current $I_{Total}$ (8/20) $\mu s$              | 20 kA                                                                              |
| Voltage protection level $U_p$ (line-line)                      | $\leq 90 V$ (C1 - 1 kV / 500 A)                                                    |
|                                                                 | $\leq 30 V$ (C3 - 25 A)                                                            |
|                                                                 | $\leq 30 V$ (C3 - 50 A)                                                            |
|                                                                 | $\leq 140 V$ (C2 - 10 kV / 5 kA)                                                   |
| Voltage protection level $U_p$ (line-earth)                     | $\leq 730 V$ (C1 - 1 kV / 500 A)                                                   |
|                                                                 | $\leq 900 V$ (C2 - 10 kV / 5 kA)                                                   |
|                                                                 | $\leq 900 V$ (C3 - 25 A)                                                           |
|                                                                 | $\leq 900 V$ (C3 - 50 A)                                                           |
| Voltage protection level $U_p$ static (line-line)               | $\leq 45 V$ (C1 - 1 kV / 500 A)                                                    |
| Response time $t_A$ (line-line)                                 | $\leq 1 ns$                                                                        |
| Response time $t_A$ (line-earth)                                | $\leq 100 ns$                                                                      |
| Input attenuation aE, sym.                                      | typ. 0.3 dB ( $\leq 10 MHz/150 \Omega$ )                                           |
| Input attenuation aE, asym.                                     | typ. 0.3 dB ( $\leq 10 MHz/150 \Omega$ )                                           |
| Cut-off frequency $f_g$ (3 dB), sym. in 150 $\Omega$ system     | typ. 60 MHz                                                                        |
| Capacity (Core-Core)                                            | typ. 30 pF                                                                         |
| Resistance per path                                             | 1.2 $\Omega \pm 5 \%$                                                              |
| Surge protection fault message                                  | Optical, multi-stage                                                               |
| Max. required back-up fuse                                      | 600 mA (FF)                                                                        |
| Impulse durability (line-line)                                  | C1 - 1 kV / 500 A                                                                  |
|                                                                 | C2 - 10 kV / 5 kA                                                                  |
|                                                                 | C2 - 10 kA                                                                         |
|                                                                 | C3 - 25 A                                                                          |

# PT-IQ-5-HF+F-5DC-PT - Surge protection device



2801292

<https://www.phoenixcontact.com/nl/products/2801292>

|                                 |                   |
|---------------------------------|-------------------|
| Impulse durability (line-earth) | C3 - 50 A         |
|                                 | C1 - 1 kV / 500 A |
|                                 | C2 - 10 kV / 5 kA |
|                                 | C2 - 10 kA        |
|                                 | C3 - 25 A         |
|                                 | C3 - 50 A         |
|                                 | D1 - 2.5 kA       |
| Pulse reset time (line-line)    | ≤ 10 ms           |
| Pulse reset time (line-earth)   | ≤ 10 ms           |

## Environmental and real-life conditions

### Ambient conditions

|                                         |                  |
|-----------------------------------------|------------------|
| Degree of protection                    | IP20             |
| Ambient temperature (operation)         | -40 °C ... 70 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |
| Altitude                                | ≤ 4000 m (amsl)  |

## Standards and regulations

|                          |                          |
|--------------------------|--------------------------|
| Standards/specifications | IEC 61643-21             |
| Note                     | 2000 + A1:2008 + A2:2012 |
| Standards/specifications | EN 61643-21              |
| Note                     | 2001 + A1:2009 + A2:2013 |
| Standards/specifications | EN 61000-6-2             |
| Note                     | 2005                     |
| Standards/specifications | EN 61000-6-3             |
| Note                     | 2007 + A1:2011           |

## Mounting

|               |                 |
|---------------|-----------------|
| Mounting type | DIN rail: 35 mm |
|---------------|-----------------|


PT-IQ-5-HF+F-5DC-PT - Surge protection device



2801292  
https://www.phoenixcontact.com/nl/products/2801292

Drawings

Dimensional drawing




Schematic diagram


| PT-IQ-2X2+F-...DC-UT(PT)                                                                                                                                                                                                                                                                                                 |                                  |                                      |                          |       |                                  |                                       |      |                          |       |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|--------------------------------------|--------------------------|-------|----------------------------------|---------------------------------------|------|--------------------------|-------|
| Category                                                                                                                                                                                                                                                                                                                 | 1oo1 architecture, HFT=0         |                                      |                          |       | 1oo2 architecture, HFT=1         |                                       |      |                          |       |
|                                                                                                                                                                                                                                                                                                                          | PFD <sub>AVG</sub>               | PFH                                  | Used budget of SIL 2 SIF |       | PFD <sub>AVG</sub>               | PFH                                   | CCF  | Used budget of SIL 3 SIF |       |
|                                                                                                                                                                                                                                                                                                                          |                                  |                                      | PFD <sub>AVG</sub>       | PFH   |                                  |                                       |      | PFD <sub>AVG</sub>       | PFH   |
|                                                                                                                                                                                                                                                                                                                          | 1.07 <sub>x10<sup>-5</sup></sub> | 1.90 <sub>x10<sup>-9</sup></sub> 1/h | 0.1 %                    | 0.2 % | 5.34 <sub>x10<sup>-7</sup></sub> | 9.50 <sub>x10<sup>-11</sup></sub> 1/h | 5 %  | 0.1 %                    | 0.1 % |
|                                                                                                                                                                                                                                                                                                                          |                                  |                                      |                          |       | 1.07 <sub>x10<sup>-6</sup></sub> | 1.90 <sub>x10<sup>-10</sup></sub> 1/h | 10 % | 0.1 %                    | 0.2 % |
| Calculation based on exida report, Phoenix Contact 13/04-032 R017 V4R0<br>exida Profile 1, FMEDA Analysis 2, T <sub>proof</sub> : 1 year, MT: 10 years, MTTR: 24 hours, PTC: 99%<br>Used standards<br>IEC/EN 61508, edition 2010 (device specific)<br>IEC/EN 61511, edition 2016 + COR1:2016 + A1:2017 (system specific) |                                  |                                      |                          |       |                                  |                                       |      |                          |       |

Functional safety scenarios  
Table also applies to the PT-IQ-5-HF+F-...DC-UT(PT) item group

Diagram



Circuit diagram



# PT-IQ-5-HF+F-5DC-PT - Surge protection device



2801292

<https://www.phoenixcontact.com/nl/products/2801292>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/nl/products/2801292>



**CSA**

Approval ID: 2761632



**UL Listed**

Approval ID: FILE E 138168



**CSAus**

Approval ID: 2761632

**Functional Safety**

Approval ID: 13-04-032 R017 V4R0

# PT-IQ-5-HF+F-5DC-PT - Surge protection device



2801292

<https://www.phoenixcontact.com/nl/products/2801292>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27171503 |
| ECLASS-15.0 | 27171503 |

### ETIM

|           |          |
|-----------|----------|
| ETIM 10.0 | EC001466 |
|-----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121600 |
|-------------|----------|

## Environmental product compliance

### EU RoHS

|                                         |                    |
|-----------------------------------------|--------------------|
| Fulfills EU RoHS substance requirements | Yes                |
| Exemption                               | 6(c), 7(a), 7(c)-I |

### China RoHS

|                                        |                                                                                                                                                                                                                                   |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Environment friendly use period (EFUP) | EFUP-50                                                                                                                                                                                                                           |
|                                        | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

### EU REACH SVHC

|                                     |                                                                |
|-------------------------------------|----------------------------------------------------------------|
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1)                                           |
|                                     | 2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol(CAS: 79-94-7) |
| SCIP                                | 3e1697e5-f45a-4f90-92b6-94ae0b1af9c4                           |