

Search within category **GO**

**BUY NOW**

**DESIGN / INSTALL**



**S050X150TAT-A**

The thermal transfer self-laminating adhesive label is made of self-extinguishing polyvinylfluoride and is supplied on a roll with 8 labels per row. The label has a white colored print-on area 0.5" (12.7 mm) high for Category 5e UTP, Category 6 UTP, Category 6e UTP, Category 5e FTP and 10 - 6 AWG wires, and a clear overlamine. It is 0.5" wide and 1.5" long (12.7 x 38.1 mm) with a 3.0" (76.2 mm) core. It comes in packages of 5000.

**Specs** **Packaging Details** **Documents** [★ Add to Favorites](#) [Add to BOM](#)

Material	Polyvinylfluoride
Maximum Wire Outside Diameter (In.)	0.32
Maximum Wire Outside Diameter (mm)	8.1
Minimum Wire Outside Diameter (In.)	0.16
Minimum Wire Outside Diameter (mm)	4
Number of Labels per Row	8
Print-On Area Height (In.)	0.5
Print-On Area Height (mm)	12.7
Overall Length (In.)	1.5
Overall Length (mm)	38.1
Overall Width (In.)	0.5
Overall Width (mm)	12.7
Color Print-on-Area	White
Length (In.)	1.50
Maximum Cable Diameter (mm)	8.1
Maximum Wire Size (AWG)	10 AWG - 6 AWG
Minimum Cable Diameter (mm)	4
RoHS Compliancy Status	Compliant
Min. Order Qty.	5,000