

Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Catalog Cut Sheet
 - PDFQL0D2Q0BA241..
 - Part Drawings
 - PDFSwitched POU..
 - Specification Sheets
 - PDF30 Amp (PViQ..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor
- Install & Maintain
 - Installation Instructions
 - PDFPanduit POU..
 - Operation Manuals
 - PDFPViQ Switches..

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips

Text Search: 'QL0B1L2BN24R1'

Your search criteria matched only one product, shown below

QL0B1L2BN24R1



- Remote switching capability for power cycling individual outlets or a group of outlets on or off to reboot equipment or power off individual outlets to stop unauthorized use
- Per outlet monitoring provides data to determine if power allocations are accurate and the efficiency metric of any server in the data center allowing individual servers to be identified as candidates for additional capacity, redeployment, or decommissioning
- Time delay sequencing avoids circuit overload due to high in-rush current at equipment start up
- Remote access to power consumption data via a web-based GUI provides global network access to real-time power information
- Integrates with Panduit® PIM™ Software which aggregates power information through a single web based GUI
- Measure in-cabinet temperature, humidity, airflow, and dew point remotely to prevent environmental factors that can cause equipment to overheat or malfunction
- Alarm messaging capability provides user-defined alarm/messaging capabilities for specific

events that exceeded thresholds

- Each outlet has a green LED for indication if the outlet is on or off for easy visual identification
- Optional remote LED display available for local monitoring, part number PVQ -RD
- Outlet Group Overload Protection allows user defined amperage threshold for a group of outlets to prevent accidental circuit breaker overload

| | |
|------------------------------|--|
| Part Number | QL0B1L2BN24R1 |
| RoHS Compliancy Status | Compliant |
| Part Description | Vertical switched power strip with per outlet power and environmental monitoring, 30 A, 208V, 18 IEC G13 and 6 IEC G19 receptacles, RJ-45 Ethernet port with two RJ12 remote environmental ports, two 20 A double pole magnetic breaker on/off switch with integral switch guard, and 10' power cord with NEMA L6-30P twist lock plug. UL and c-UL Listed. Dimensions: 70"H x 2.5"W x 2.3"D (1778mm x 64mm x 57mm) |
| Product Type | Vertical Power Outlet Unit |
| Color | Black |
| CE Compliant | No |
| Plug Type | NEMA L630P |
| Pricing Description | Vertical Mixed (18) C-13 & (6) C-19 Switched with per Outlet Power & Environmental Monitored 208V, 30A SinglePhase POU |
| Min. Order UOM | PC |
| Min. Order Qty. | 1 |
| Voltage | 208V |
| BOM Qty. (# of Pkgs.) | <input type="text" value="0"/> |
| Add to Favorite Product List | <input type="button" value="e"/> |

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.