

1SET411204R0000 ✓ ACTIVE

ENTRELEC

TE Internal #: 1SET411204R0000

Wiring Duct Cover, PVC, 8.9 mm [.35 in] Height, 2000 mm [78.74 in]

Length, 80 mm [3.15 in] Width, -5 – 60 °C [23 – 140 °F]

[View on TE.com >](#)



Wire Protection & Management > Wiring Ducts & Accessories > Wiring Ducts & Covers > Wiring Duct Covers: PVC, Gray, 2 meters [2000mm]



Wiring Duct Product Type: **Wiring Duct Cover**

Primary Product Material: **PVC**

Product Height: **8.9 mm [.35 in]**

Product Length: **2000 mm [78.74 in]**

Product Width: **80 mm [3.15 in]**

[All Wiring Duct Covers: PVC, Gray, 2 meters \[2000mm\] \(6\)](#)

Features

Product Type Features

Wiring Duct Product Type	Wiring Duct Cover
--------------------------	-------------------

Body Features

Primary Product Color	Gray
Primary Product Material	PVC

Dimensions

Product Height	8.9 mm[.35 in]
Product Length	2000 mm[78.74 in]
Product Width	80 mm[3.15 in]

Usage Conditions

Operating Temperature Range	-5 – 60 °C[23 – 140 °F]
-----------------------------	-------------------------

Packaging Features

Packaging Quantity	3
--------------------	---

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Out of Scope
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # CAT-Z62-W1-DP
PVC Wiring Duct: 2 meters, Gray
Color, Flame-Retardant

Customers Also Bought



TE Part #T4111001041-000
RPC-M12-MS-4CON-PG7-MU



TE Part #T4110001041-000
M12,FEMALE,STRAIGHT,A CODE,4P,
PG7,GOLD



TE Part #1SNA115541R1100
D2.5/6.DA



TE Part #1SET411203R0000
WD-1-CP-GR060




TE Part #1SNA115116R0700
M4/6



TE Part #321895
SOLIS R HT 22-16COMM22-18MIL 8



TE Part #322335
TERMINAL,SOLIS R HT 16-14 10



TE Part #322733
TERMINAL,SOLIS R HR 16-14 1/4



TE Part #9-1419111-1
PT570730



TE Part #2-1676914-2
YR1 0.1% 3K83

Documents

Product Drawings

[WD-1-CP-GR080](#)

French

CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_1SET411204R0000_A.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1SET411204R0000_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1SET411204R0000_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

1SET411204R0000

Wiring Duct Cover, PVC, 8.9 mm [.35 in] Height, 2000 mm [78.74 in] Length, 80 mm [3.15 in] Width, -5 – 60 °C [23 – 140 °F]



[Infographic - entrelec ews-linecard](#)

English

[Datasheet - ENTRELEC-wiring-duct-DS](#)

English

[Datasheet - Entrelec Electrical-Solutions](#)

[Essential Entrelec Terminal Blocks](#)

French

[Essential Entrelec Terminal Blocks](#)

English

[Essential Entrelec Terminal Blocks](#)

Japanese

[Agency Approvals](#)

[Agency Approval Document](#)

English