

Accessories
MB M3/M5 CRM**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com**Product image****Building installation wiring**

For building installations, we offer a complete system that revolves around the 10×3 copper rail and comprises perfectly coordinated components: from installation terminal blocks, neutral conductor terminal blocks and distribution terminal blocks to comprehensive accessories such as busbars and busbar holders.

General ordering data

Type	MB M3/M5 CRM
Order No.	0503500000
Version	Accessories, Sliding nut, Polyamide 66
GTIN (EAN)	4008 190 182083
Qty.	20 pc(s).

**Accessories
MB M3/M5 CRM**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

Width	12 mm	Width (inches)	0.472 inch
Height	25 mm	Height (inches)	0.984 inch
Depth	14 mm	Depth (inches)	0.551 inch
Net weight	3.55 g		

Temperatures

Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	100 °C
----------------------------------	--------	----------------------------------	--------

Material data

Material	Polyamide 66	Surface finish	untreated
Colour	Cream	UL 94 flammability rating	V-2

System specifications

Version	For the mounting rails	Rail	TS 32
---------	------------------------	------	-------

Additional technical data

Explosion-tested version	No	Type of fixing	Snap-on
--------------------------	----	----------------	---------

Dimensions

Metric size of the thread, external	0 M3.0	Pitch in mm (P)	12 mm
-------------------------------------	--------	-----------------	-------

Classifications

ETIM 6.0	EC000096	ETIM 7.0	EC000096
eClass 9.0	23-11-08-04	eClass 9.1	23-11-08-04
eClass 10.0	23-11-08-04	UNSPSC	30-21-18-11

Approvals

ROHS	Conform
------	---------

Downloads

Brochure/Catalogue	CAT 1 TERM 16/17 EN
Engineering Data	EPLAN, WSCAD
User Documentation	StorageConditionsTerminalBlocks