Metal Element Current Sense Resistor

ULR Series



Features

- Robust metal strip able to withstand high temperature and high current.
- Power ratings up to 5W
- Low TCR and Inductance
- Resistance Range from 0.15mΩ to 10mΩ
- RoHS compliant
- AEC-Q200
- Higher wattage devices feature PCB clearance gap to maximize thermal performance

All parts are Pb-free and comply with EU Directive 2011/65/EU amended by (EU) 2015/863 (RoHS3)

Electrical Data

Type	Size	Coating	Power Rating [3](W)	Standard Resistance Value mΩ[1]	TCR (ppm/°C)	Tolerance (%)	Dielectric Withstanding Voltage (V	Ambient Temperature (°C)
ULRG1 / ULR1S	1206	Green Underside	1	0.2, 0.25, 0.3, 0.4, 0.5, 0.6	200	1, 5	N/A	-55 to +170
				0.75, 1, 1.2, 2, 2.5, 3, 3.5, 4, 5, 5.5, 6, 7, 8, 9, 10	50			
ULRG15 / ULR15S	2010		1.5	0.2, 0.25, 0.3, 0.4, 0.5	150			
				0.75, 1, 1.5, 2, 2.5, 3, 4, 5, 5.5, 6, 7, 8, 9, 10	50			
ULR2N	1020		2	1	300			
				1.5, 2, 2.5, 3	170			
ULRG2 / ULR2	2512		2	6.5, 7, 7.5, 8, 9, 10	50			
ULRG25 / ULR25			2.5	3.5, 4, 4.5, 5, 5.5, 6				
ULRG3 / ULR3			3	0.15, 0.25, 0.3, 0.4, 0.5, 0.75	150			
				1, 1.5, 2, 2.5, 3	50			
ULR5			5[2]	0.5, 0.75	150			
				1, 1.5, 2, 2.5, 3	50			
ULR3N	1225		3	0.1	500			
				0.2, 0.25, 0.3, 0.4	350			
				0.5	300			
				0.7, 0.75, 0.8, 0.9, 1.0	250			
				1.5, 2.0, 2.5, 3.0	100			
ULRB1 / ULR1	2512	Black	1	0.5, 0.75, 1, 1.5, 2	50		200	
				2.5, 3, 3.5	150			
				1, 5, 10	100			
				6, 6.5, 7	75			
ULRB2 / ULR2			2	0.5, 0.75, 1, 1.5, 2	50			
				2.5, 3	150			

Notes: 1. For higher resistance values please refer to LRMA series.
Notes: 2. Terminal temp must not exceed 110°C
Notes: 3. Green Underside parts are rated at 80°C. Black parts are rated at 70°C.

Performance Data

AEC-Q200 Table 7		Method		Max. (add R0005)		
ref.	Test[1]			Black	Green Underside	
					1206 & 2010	1020, 2512 & 1225
3	High Temp. Exposure *	MIL-STD-202 Method 108	ΔR%	1		
4	Temperature Cycling	JESD22 Method JA-104	ΔR%	0.5		1
6	Moisture Resistance	MIL-STD-202 Method 106	ΔR%	1		
7	Biased Humidity	MIL-STD-202 Method 103	ΔR%	1		
8	Operational Life (Cyclic Load) *	MIL-STD-202 Method 108	ΔR%	1		
14	Vibration	MIL-STD-202 Method 204	ΔR%	0.5		1
15	Resistance to Soldering Heat *	MIL-STD-202 Method 210	ΔR%	0.5		1
16	Thermal Shock *	MIL-STD-202 Method 107	ΔR%	0.5		1
18	Solderability	J-STD-002		>95% coverage		
21	Board Flex	AEC-Q200-005	ΔR%	0.5		1
22	Terminal Strength	AEC-Q200-006	ΔR%	0.25		1
	Short Term Overload *	5 x Pr for 5s	ΔR%	0.5		1
	Resistance to Sulphur-Bearing Gas[2]	EIA-977	ΔR%	N/A	1	

Notes: 1. Full AEC-Q200 qualification applies to 2512 size. The 1206 and 2010 sizes have received the tests marked *.
2. Resistance to sulphur bearing gas has been tested for green underside construction only.

General Note
TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

© TT Electronics plc

Metal Element Current Sense Resistor

ULR Series

Physical Data

Dimensions(mm) and weight (mg)

Size	Coating	Values	L (±0.25)	W	T (±0.2)	D	Wt (nom)
1206	Green Underside	0.2, 0.25	3.2	1.6 ±0.3	1.0	1.5 ±0.25	25
		0.3, 0.4				1.4 ±0.25	
		0.5, 0.6		1.6 ±0.1	0.6	1.35 ±0.25	20
		0.75				1.23 ±0.25	
		1, 1.2, 3.5, 4, 5, 5.5, 6				1.1 ±0.25	
		2, 2.5, 3, 10				0.6 ±0.25	
		7, 8, 9				0.9 ±0.25	
2010		0.2	5.08	2.54 ±0.3	1.0	2.34 ±0.25	50
		0.25				2.24 ±0.25	
		0.3				2.04 ±0.25	
		0.4				1.84 ±0.25	
		0.5		2.54 ±0.15	0.6	2.17 ±0.25	40
		0.75				2.04 ±0.25	
		1, 1.5, 4, 5, 5.5				1.84 ±0.25	
		2, 2.5, 6, 7, 8				1.54 ±0.25	
		3				1.04 ±0.25	
		9, 10				1.29 ±0.25	
1020		1, 1.5, 2, 2.5, 3	2.54	5.08±0.25	0.6	0.57 ±0.25	45
2512		0.15	6.35	3.0 ±0.3	1.0	2.98 ±0.25	59
		0.2				2.88 ±0.25	
		0.25, 0.3				2.68 ±0.25	
		0.4				2.18 ±0.25	
		0.5		3.0 ±0.2	0.6	2.68 ±0.25	
		0.75				2.48 ±0.25	
		1, 5, 5.5, 6				1.93 ±0.25	
		2, 2.5, 3, 3.5, 8, 9, 10				1.18 ±0.25	
		4, 4.5				2.18 ±0.25	
		1.5, 6.5, 7, 7.5				1.43 ±0.25	
1225		0.1, 0.2,	3.0	6.35±0.25	1	1.0±0.25	65
		0.25, 0.3, 0.4			1	0.5±0.25	
		0.5, 0.7, 0.75, 0.8, 0.9, 1.0			0.6	0.5±0.25	
		1.5			0.6	1.0±0.25	
		2			0.6	0.8±0.25	
		2.5, 3			0.6	0.5±0.25	
2512	Black	0.5	6.35	3.18 ±0.25	1.25	1.85 ±0.38	184
		0.75			0.75	1.55 ±0.38	131
		1			0.65		111
		1.5			0.45		69
		2			0.35		49
		2.5			0.65	1.4 ±0.38	98
		3			0.55		83
		4			0.45		63
		5			0.35		50
		6			0.32		42
		6.5			0.3		36
		7			0.27		34
		10			0.25		26



General Note
TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

BI Technologies IRC Welwyn

www.ttelectronics.com/resistors

© TT Electronics plc

Metal Element Current Sense Resistor

ULR Series

Construction

Black Coat
A low TCR resistance alloy plate, with tin plated connection bands is protectively coated on the upper and lower faces and numerically marked with the resistance value. This part is suitable for wave or reflow soldering.

Green Underside Coat
A low TCR resistance alloy plate is grooved to set the final resistance and the lower face only is protected with an epoxy coating. The lower faces are tin plated for connections. This part is ONLY suitable for reflow soldering.

Marking
Only black coated parts are marked. For values which are integer numbers of milliohms, the marking is 4-character IEC62 code; e.g. “R002” for 2mΩ, “R010” for 10mΩ. For values including fractions of a milliohm the marking is 3 or 4-character code using “M” to indicate the decimal point, e.g. “M75” for 0.75mΩ, “1M50” for 1.5mΩ.



Black Coat



Green Underside Coat

Termination Details:

Material	Matt tin plated finish over copper.
Solderability	95% min coverage (MIL-STD 202F / 208H, 245ºC for 3 secs)

Power Derating Curves





Notes

The power derating curve is a guidance based on a conservative design model. The ULR is a solid metal alloy construction that can withstand significantly greater operating temperatures than the conservative model permits. The protective coating will operate up to 260°C and the alloy can withstand in excess of 350°C. Therefore, the system thermal design will be a more significant design parameter due to the heat limitations of the solder joint.

Full power dissipation is achievable with the part mounted on 120x51mm high-Tg FR4 board with 70µm inner and outer planes. Alternative mounting arrangements may be used, provided the heatsinking effect permits a combination of power dissipation and terminal temperature within the derating curve shown.

General Note
TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics’ own data and is considered accurate at time of going to print.

© TT Electronics plc

Metal Element Current Sense Resistor

ULR Series

Recommended Layouts and Measurement Probe Positions

4 pad layout



2 pad layout



4-wire measurement probe positions



Size	Coating	Values	a	b	c	L	d	e	f
1206	Green Underside	0.5, 0.6, 1, 4 - 6	1.55	0.5	0.7	0.55	1.9	2.6	1.25
		2 - 3, 10	1.05			1.55			
		7 - 9	1.35			0.95			
2010		0.5	2.61	0.8	1.05	0.3	2.9	4.32	1.2
		1, 4 - 5	2.29			0.95			
		2, 6 - 8	1.99			1.55			
		3	1.49			2.55			
		9 - 10	1.74			2.05			
1020		1, 1.5, 2, 2.5, 3	0.925	0.8	2.365	1.04	5.53	2	1.77
2512	Black	All	2.7	1.0	1.45	2.95	3.6	5.4	1.5
2512	Green Underside	0.5	3.13		1.2	0.54	3.45		
		0.75	2.93			0.94			
		1	2.38			2.04			
		1.5	1.88			3.04			
		2 - 3	1.63			3.54			
		4, 4.5	2.63			1.54			
		5 - 6	2.38			2.04			
		6.5, 7	1.88			3.04			
		8 - 10	1.63			3.54			
1225		0.1 - 0.25	1.4	0.8	3.0	0.6	6.8	2.0	2.25
		0.3 - 1.0	0.9			1.6			
		1.5	1.4			0.6			
		2.0	1.2			1.0			
		2.5, 3.0	0.9			1.6			

Note: These resistors are designed to have the correct ohmic value when mounted on a PCB. Probed measurements may read higher values and mounting offsets may need to be established to account for this, especially with sub-milliohm values.

Symmetrical Kelvin Connected (4-Wire) Alternatives

Package	Resistance (mΩ)	a	b	c	d	e	f
1206	0.2 - 0.4	0.75	1.9	0.4	0.6	2.15	0.6
2010	0.2 - 0.4	1.35	2.89	1.4	0.6	3.08	0.6
2512 - Green Underside	0.15 - 0.3	2	3.4	1.0	0.6	2.8	0.6
	0.4	1.5	3.4	2.0	0.6	3.8	0.6



Vias with copper traces on internal layers



Sense traces on solder pads beneath the chip



General Note
TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

© TT Electronics plc

Packaging



Type	Resistance (mΩ)	A	B	W	E	F	P0	P1	P2	ØD0	ØD0	T	Quantity (EA)
1206	<0.5	1.90 ± 0.1	3.60 ± 0.1	8.0 ± 0.2	1.75 ± 0.1	3.5 ± 0.05	4.0 ± 0.1	4.0 ± 0.1	2.0 ± 0.05	1.55 ± 0.05	1.0min	1.25 ± 0.1	2000 on 7" reel
	≥0.5											0.87 ± 0.1	
2010	<0.5	2.85 ± 0.1	5.55 ± 0.1	12.0 ± 0.2	1.75 ± 0.1	5.5 ± 0.05	4.0 ± 0.1	4.0 ± 0.1	2.0 ± 0.05	1.55 ± 0.05	1.5min	1.35 ± 0.1	
	≥0.5											0.85 ± 0.1	
1020	1 - 3												
2512 Black	0.50 - 0.75	3.40 ± 0.1	6.75 ± 0.1	12.0 ± 0.1	1.75 ± 0.1	5.5 ± 0.05	4.0 ± 0.1	4.0 ± 0.1	2.0 ± 0.05	1.55 ± 0.05	1.4min	1.45 ± 0.2	
	>0.75											0.81 ± 0.1	
2512 Green Underside	<0.5	3.40 ± 0.1	6.75 ± 0.1	12.0 ± 0.3	1.75 ± 0.1	5.5 ± 0.05	4.0 ± 0.1	4.0 ± 0.1	2.0 ± 0.05	1.55 ± 0.05	1.5min	1.4 ± 0.1	
	≥0.5											0.8 ± 0.1	
1225	0.1- 0.4	3.40 ± 0.1	6.75 ± 0.1	12.0 ± 0.3	1.75 ± 0.1	5.5 ± 0.05	4.0 ± 0.1	4.0 ± 0.1	2.0 ± 0.05	1.55 ± 0.05	1.5min	1.2 ± 0.1	
	0.5-3.0											0.80 ± 0.1	

Note:

1. The cumulative tolerance of 10 sprocket hole pitch is ± 0.2 mm.
2. Carrier camber shall not be more than 1 mm per 100 mm through a length of 250 mm.
3. A & B measured 0.3 mm from the bottom of the packet.
4. T measured at a point on the inside bottom of the packet to the top surface of the carrier.
5. Pocket position relative to sprocket hole is measured as the true position of the pocket and not the pocket hole.

General Note
TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

© TT Electronics plc

Metal Element Current Sense Resistor

ULR Series

Ordering Procedure

This product has two valid part numbers:

European (Welwyn) Part Number: ULR2-R0015FT2 (2512, 1.5 milliohms ±1%, Pb-free)

U	L	R	2	-	R	0	0	1	5	F	T	2
1					2					3	4	

1 Type	2 Value	3 Tolerance	4 Packing	
ULR1S, ULR1, ULR15S, ULR2N, ULR2, ULR25, ULR3, ULR3N, ULR5	3 to 6 characters R = ohms	F = ±1%	T2 = Plastic tape	
		J = ±5%	All sizes	2000/reel

USA (IRC) Part Number: ULRB22512R0015FLFSLT (2512, 1.5 milliohms ±1%, Pb-free)

U	L	R	B	2	2	5	1	2	R	0	0	1	5	F	L	F	S	L	T
1					2				3					4	5		6		

1 Type	2 Size	3 Value	4 Tolerance	5 Termination	6 Packing	
ULRG1, ULRG15, ULRG2, ULRG25, ULRG3, ULRB1, ULRB2	1206	4 - 6 characters R = ohms	F = ±1%	LF = Pb-free	SLT = Plastic tape	
	2010		J = ±5%		All sizes	2000/reel
	2512					

General Note
TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

© TT Electronics plc