

Style E 6.3 (1/4").

**7045 Z** Professional bit, TORX®, style E 6.3.

Material: High grade chrome-vanadium steel, through hardened.
 Drive: DIN 3126, ISO 1173, style E 6.3.
 Application: For all types of screw applications in trade and industry.
 Extra: Overlength bits in lengths of 50, 70, 90, 110 and 150 mm.

Order-No.	⊗	↔		
39184	T1	50	NEW	5
39185	T2	50	NEW	5
39186	T3	50	NEW	5
39187	T4	50	NEW	5
32299	T5	50		5
32302	T6	50		5
33709	T6	70		5
33717	T6	90		5
38370	T6	150	NEW	5
32303	T7	50		5
33710	T7	70		5
33718	T7	90		5
38371	T7	150	NEW	5
32304	T8	50		5
33711	T8	70		5
33719	T8	90		5
36327	T8	150	NEW	5
32305	T9	50		5
33712	T9	70		5
33720	T9	90		5
38372	T9	150	NEW	5
32306	T10	50		5
33713	T10	70		5
33721	T10	90		5
33725	T10	110		5
33726	T10	150		5
32307	T15	50		5
33714	T15	70		5
33722	T15	90		5
33727	T15	110		5
33728	T15	150		5
32308	T20	50		5
33715	T20	70		5
33723	T20	90		5
33729	T20	110		5
33730	T20	150		5
32309	T25	50		5
33716	T25	70		5
33724	T25	90		5
33731	T25	110		5
33732	T25	150		5
33920	T27	50		5
33921	T27	70		5
33922	T27	90		5
33923	T30	50		5
33924	T30	70		5
33925	T30	90		5
33926	T30	110		5
33927	T30	150		5
33928	T40	50		5
33929	T40	70		5
33930	T40	90		5
33931	T40	110		5
33932	T40	150		5

Style E 6.3 (1/4").

**7045 Z TR** Professional bit, TORX® H, style E 6.3.

Material: High grade chrome-vanadium steel, through hardened.
 Drive: DIN 3126, ISO 1173, style E 6.3.
 Application: For all types of screw applications in trade and industry.
 Extra: Hole in the bit tip for TORX® Tamper Resistant security screws.

Order-No.	⊗	↔		
21045	T7H	50		5
21047	T8H	50		5
20218	T9H	50		5
20219	T10H	50		5
39188	T10H	90	NEW	5
24867	T15H	50		5
39189	T15H	90	NEW	5
20220	T20H	50		5
39190	T20H	90	NEW	5
20221	T25H	50		5
39191	T25H	90	NEW	5
20222	T27H	50		5
39192	T27H	90	NEW	5
20223	T30H	50		5
39193	T30H	90	NEW	5
20224	T40H	50		5
39194	T40H	90	NEW	5

**7048 Z** Professional bit, Robertson, style E 6.3.

Material: High grade chrome-vanadium steel, through hardened.
 Drive: DIN 3126, ISO 1173, style E 6.3.
 Application: For all types of screw applications in trade and industry.
 Extra: A tapered tip allows for easy insertion of the bit into the screw.

Order-No.	⊗	⊙	↔	
06637	Robertson 1	2.3	50	5
39206	Robertson 1	2.3	90 NEW	5
06638	Robertson 2	2.8	50	5
39207	Robertson 2	2.8	90 NEW	5
06639	Robertson 3	3.3	50	5
39208	Robertson 3	3.3	90 NEW	5